

**Sensor Fusion for Shape Sensing
Theory and Numerical Simulation**

Mooij, Cornelis; Martinez, Marcias; Benedictus, Rinze

Publication date

2016

Document Version

Publisher's PDF, also known as Version of record

Citation (APA)

de Mooij, C., Martinez, M., & Benedictus, R. (2016). Sensor Fusion for Shape Sensing: Theory and Numerical Simulation. Poster session presented at 27th International Conference on Adaptive Structures and Technologies, Lake George, United States.

Important note

To cite this publication, please use the final published version (if applicable).
Please check the document version above.

Copyright

Other than for strictly personal use, it is not permitted to download, forward or distribute the text or part of it, without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license such as Creative Commons.

Takedown policy

Please contact us and provide details if you believe this document breaches copyrights.
We will remove access to the work immediately and investigate your claim.

Sensor Fusion For Shape Sensing: Theory and Numerical Results

Cornelis de Mooij^{1*}, Marcias Martinez^{2,1}, Rinze Benedictus¹

¹Structural Integrity & Composites, Faculty of Aerospace Engineering, Delft University of Technology, Delft, The Netherlands


²Department of Mechanical and Aeronautical Engineering, Clarkson University, Potsdam, NY, USA

Introduction

An inverse finite element (iFEM) algorithm was developed for shape sensing. The algorithm uses result smoothing through Tikhonov regularization while compensating for missing sensor data/measurements. In this study, a cantilever plate subjected to a point bending load is considered. The aim of this study is to accurately determine global strain distributions with as few sensors as possible.

Method

The iFEM algorithm compares numerical strains and/or displacements to those obtained from sensors mounted on the structure or simulated based on FEA results. This is shown in the flowchart below:



The iFEM error functional is based on the squared differences between the numerical and the measured values:


$$\Phi = C_e \| \mathbf{e} - \mathbf{e}^\varepsilon \|^2 + C_d \| \mathbf{q} - \mathbf{q}^\varepsilon \|^2$$

C_e and C_d are weight factors, \mathbf{e} and \mathbf{q} are numerical strains and displacements and \mathbf{e}^ε and \mathbf{q}^ε are sensor data.


The error functional is minimized by taking the derivatives with respect to the structural degrees of freedom. The resulting system of linear equations is solved with Gaussian elimination, similar to the classical FE approach. The strains are then calculated from the displacements.

Set-up

The plate consists of a clamped aluminum cantilever plate under a point bending load as shown in the figure below.




The displacement sensors were placed semi-randomly, avoiding clustering. This results in most sensors being near the edges.




Result

FEA and iFEM results are shown for a point-loaded cantilever plate. The iFEM analysis used 10 sensors. The maximum deflection has an error of 0.17%, compared to 0.4% with 28 sensors (Kefal et al. 2016). The distortion on the left is due to the optimization focussing on areas with large displacements.



Over-all Result

The value of the error functional is plotted against the number of sensors. Each dot is a separate iFEM analysis.



Two things stand out: sometimes, with no apparent pattern, a highly inaccurate result is obtained. Second, even with quite a small number of sensors, an accurate estimate of the displacements can be obtained for a simple load case and a simple structure.

Conclusion

The new iFEM algorithm results were compared to those found in the literature. While the new approach can achieve greater accuracy with fewer sensors than the results presented in the literature, it also shows a lack of reliability, which is believed to be due to the random nature of the sensor placement and the interpolation technique that was utilized.

Acknowledgements:

This work was carried out as part of the Monitoring of Aerospace Structural Shapes project (MASS) funded under the FP7 Marie Curie Career Integration Grant (Grant no. 618316). Special thanks to Dr. Fred Vermolen and Prof. Sotiris Koussios at the Delft University of Technology for their valuable advice.

