

Aluminium-organic matter precipitation as a geoengineering tool for in situ permeability reduction in a porous media

Laumann, Susanne; Zhou, Jiani; Heimovaara, Timo

Publication date

2016

Document Version

Final published version

Citation (APA)

Laumann, S., Zhou, J., & Heimovaara, T. (2016). *Aluminium-organic matter precipitation as a geoengineering tool for in situ permeability reduction in a porous media*. 1689-1689. Abstract from 26th Goldschmidt Conference, Yokohama, Japan.

Important note

To cite this publication, please use the final published version (if applicable). Please check the document version above.

Copyright

Other than for strictly personal use, it is not permitted to download, forward or distribute the text or part of it, without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license such as Creative Commons.

Takedown policy

Please contact us and provide details if you believe this document breaches copyrights. We will remove access to the work immediately and investigate your claim.

Aluminium-organic matter precipitation as a geoengineering tool for *in situ* permeability reduction in a porous media

S. LAUMANN, J. ZHOU AND T.J. HEIMOVAARA¹

¹ Section of Geo-engineering, Faculty of Civil Engineering and Geosciences, Delft University of Technology (*correspondence: s.j.laumann@tudelft.nl)

The utilization of natural processes for engineering purposes has been widely discussed in recent years since they might enable the development of cost-effective, robust and environmentally compatible engineering technologies. Biomineralization is one of the many possible biogeochemical processes that is currently investigated in detail. We propose the use of another natural process, namely podzolisation, as a novel geoengineering tool for *in situ* permeability reduction.

Podzolisation is a soil formation process where the mobilization and subsequent leaching of aluminium, iron and organic matter (OM) in the topsoil is followed by their precipitation at greater depth. The accumulation of Al/Fe-OM precipitates results in the formation of an almost impermeable soil layer [1].

In situ permeability reduction is interesting for several engineering questions, e.g., prevention of piping, leaking water bodies, and contaminant spreading.

Preliminary experiments and modelling results revealed that Al-OM precipitates can reduce the hydraulic conductivity in sand by up to 4 orders of magnitude. In order to apply the podzolisation process for engineering purposes, it is, however, necessary to control the reaction kinetics and ensure Al-OM precipitation over the entire desired treatment zone within a porous media. Therefore, a 2D experimental setup (80x160x5 cm) equipped with numerous pressure and electrical resistance tomography (ERT) sensors is used to test different kinds of injection strategies and their effect on the permeability reduction within a porous media.

A reactive transport model coupling a MATLAB-based toolbox and ORCHESTRA (equilibrium reaction processor) is used (1) to design the injection strategies and (2) to simulate the solute transport, the geochemical reactions and their effect on the permeability within the experimental setup. The experimental results will be used to validate the model and to implement the most promising injection strategy in the field.

[1] U.S. Lundstroem, N. van Breemen, D.Bain, *Geoderma* 94, 2000, 91-107