

Method and system for managing a technical installation

RamaKrishnaraja, Prithvi Raj; Kamboj, Vineet; Mehrotra, Siddharth

Publication date

2019

Document Version

Final published version

Citation (APA)

RamaKrishnaraja, P. R., Kamboj, V., & Mehrotra, S. (2019). IPC No. WO2019197434A1. Method and system for managing a technical installation. World Intellectual Property Organization.

Important note

To cite this publication, please use the final published version (if applicable).
Please check the document version above.

Copyright

Other than for strictly personal use, it is not permitted to download, forward or distribute the text or part of it, without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license such as Creative Commons.

Takedown policy

Please contact us and provide details if you believe this document breaches copyrights.
We will remove access to the work immediately and investigate your claim.



(51) **International Patent Classification:**
G05B 23/02 (2006.01)

(21) **International Application Number:**
PCT/EP20 19/05901 1

(22) **International Filing Date:**
10 April 2019 (10.04.2019)

(25) **Filing Language:** English

(26) **Publication Language:** English

(30) **Priority Data:**
18166571.2 10 April 2018 (10.04.2018) EP

(71) **Applicant:** SIEMENS AKTIENGESELLSCHAFT [DE/DE]; Werner-von-Siemens-Stralk 1, 80333 Munchen (PE).


(72) **Inventors:** RAMAKRISHNARAJA, Prithvi Raj; Beside Medchal RTO Office, Dandamudi Enclave, Jeedimetla Village, C/O P R K RAJA, 207-B Block, BHEL Colony, 500067 Secundrabad, AP (IN). KAMBOJ, Vineet; HUDA Jagadhri, Yamunanagar, No. 1382, Sector-17, 135003 Haryana (IN). MEHROTRA, Siddharth; Near Kotwali, Mehrotra & Son's, Moti Chowk, 242001 Shahjahanpur, Uttar Pradesh (IN).

(74) **Agent:** ISARPATENT - PATENT- UND RECHTSANWÄLTE BEHNISCH BARTH CHARLES HASSA PECKMANN UND PARTNER MBB; Friedrichstralk 31, 80801 Munchen (DE).

(81) **Designated States** (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN,

(54) **Title:** METHOD AND SYSTEM FOR MANAGING A TECHNICAL INSTALLATION

FIG 1



(57) **Abstract:** A method (300) and system (101) for managing a technical installation (108) are disclosed. In one aspect of the invention, an event associated with at least a portion of the technical installation (108) is detected based on sensor data associated with the portion of the technical installation (108). In another aspect of the invention, a representative view (1101) of the portion of the technical installation (108) is rendered on at least one wearable device (107a-c), wherein the representative view (1101) displays information associated with the detected event in conjunction with the multi-dimensional view of the portion of the technical installation (108). In yet another aspect of the invention, a predictive time series analysis of the sensor data associated with the detected event is generated. In another aspect of the invention, the predictive time series analysis in conjunction with the representative view (1101) of the at least one portion of the technical installation (108) is displayed.



HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report (Art. 21(3))*

METHOD AND SYSTEM FOR MANAGING A TECHNICAL INSTALLATION

Description

5

The present invention relates to a method and system for managing a technical installation. The method includes detecting an event associated with a portion of the technical installation based on sensor data associated with the portion of the technical installation and rendering a representative view of the portion of the technical installation on a weara-
10 ble device, wherein the representative view displays information associated with the detected event in conjunction with the multi-dimensional view of the portion of the technical installation.

Situational awareness is cognizance of environmental elements and events with respect
15 to time or space. Such cognizance involves comprehending the elements and the events and projecting the status of such elements and events when a variable affecting the elements or the events is changed. Technical installations may be remotely located, for example offshore locations, sea-beds and deserts. Such technical installations may involve several complex workflows for its operation. Multiple events may occur at a given point in
20 time on the technical installation, which require immediate attention of at least one entity. Identification of the cause of an anomaly in complex technical installation is of utmost importance. Such identification may involve several aspects such as detection of the problem, detection of the portion in the technical installation where the anomaly has occurred, and comprehending the anomaly and the cause of the anomaly. However, factors such as
25 distance of the entity from the location of the event or occurrence of more than one event at the same time increases the difficulty identifying the anomaly. This makes the process of maintaining a technical installation cumbersome. European Patent Application EP 2884363 A2 discloses an anomaly detecting method and apparatus which excludes any anomaly data found in learned data in order to set a proper threshold for anomaly detec-
30 tion based on a model using multi-dimensional time series sensor signals. However, this patent application fails to disclose a method to resolve anomalies by identifying one or more appropriate mitigation actions. Failure to resolve the pending events may lead to catastrophic accidents, thereby causing loss of life and property. Furthermore, determination of an appropriate mitigation action for the anomaly is also challenging in maintenance
35 of the technical installation. Implementation of an unsuitable mitigation action may lead to failure of the technical installation and permanent damage to multiple portions of the installation. Therefore, it is essential to accurately detect, comprehend and project events

which occur in the installation such that an accurate decision to mitigate the anomaly is made.

5 In the light of the above, there exists a need to provide a method and system for managing a technical installation that is capable of detecting, comprehending and projecting the anomaly and the mitigation actions.

10 The object of the invention is therefore to provide a method and a system for managing a technical installation which supports human cognition efficiently and accurately.

This object is solved by a method of managing a technical installation, a system, a computer program product which generates a predictive time series analysis of the sensor data to manage the technical installation.

15 In the following, the solution according to the invention is described with respect to the claimed system as well as with respect to the claimed method. Features, advantages or alternative embodiments herein can be assigned to the other claimed objects and vice versa. In other words, claims for the system can be improved with features described or claimed in the context of the method. In this case, the functional features of the method
20 are embodied by objective units of the system.

Based on the abovementioned method, the invention achieves the object of the invention by generating a predictive time series analysis of the sensor data associated with the detected event and displaying the predictive time series analysis in conjunction with representative
25 view of the at least one portion of the technical installation. An advantage of the invention is that the method provides quick access to necessary data pertaining to the anomalous portion of the technical installation. Another advantage of the invention is that the predictive time series analysis information is provided in conjunction with representative view of the portion of the technical installation, thereby amplifying the perception of
30 the anomaly. This enables an efficient decision making process.

The present invention describes a method of managing a technical installation. The method comprises a step of detecting an event associated with a portion of the technical installation based on sensor data associated with the portion of the technical installation. One
35 or more sensors may be disposed in at least a portion of the technical installation. The one or more sensors may be adapted to receive one or more values associated with the technical installation which may correspond to the functioning of the technical installation.

Such values may be related to one or more parameters, for example, but not limited to pressure, temperature, flow and control. These parameters are monitored to determine the functioning of the technical installation. Based on the parameter values obtained from the sensors, an event may be detected in the portion of the technical installation. The event may be, for example, an anomaly or abnormality in the working of the technical installation. The method also includes a step of rendering a representative view of the portion of the technical installation on a wearable device. The representative view may display information associated with the detected event in conjunction with the multi-dimensional view of the portion of the technical installation. According to an embodiment of the invention, the representative view may be, for example a holographic view. A hologram is a photographic recording of a light field that is used to display a multi-dimensional image of the holographed subject. In an embodiment of the invention, a hologram of the portion of the technical installation is generated using methods well-known in the art. The holographic view of the portion of the technical installation is coupled with information pertaining to the detected event. For example, if a unit in the portion of the technical installation is malfunctioning, information related to such malfunctioning unit may be overlaid on the multi-dimensional view of the technical installation. The information may be, for example, one or more parameters associated with the functioning of the unit in the technical installation. The values for each of the parameters may be displayed in conjunction with the holographic view of the portion of the technical installation. This enables an entity to determine the cause of the malfunction of the unit. In another embodiment of the invention, the malfunctioning unit may be indicated, for example, with a different color or as a hologram in motion. The hologram in motion may for example be a pulsating motion such that the malfunctioning unit of the technical installation appears to pulsate. The advantage of rendering a holographic view is that the detected event in the portion of the technical installation can be located easily. This enables identification of the malfunctioning unit within the technical installation efficiently.

The method further comprises a step of generating a predictive time series analysis of the sensor data associated with the detected event. A predictive time series analysis refers to determination of how an event would progress over a period of time. Sensor data refers to data associated with the technical installation and may include values associated with one or more parameters related to the functioning of the technical installation. The predictive analysis is based on a time series analysis. The values associated with the parameters of the unit have a threshold. The threshold determines the permissible limits within which the values of the parameters may lie for effective functioning of the unit of the technical installation. A predictive model divides the limits based on time to produce a predictive time

series analysis based on the sensor data associated with the detected event. The predictive time series analysis advantageously enables the entity to determine how the event would progress over a period of time. Predictive time series analysis also allows the entity to identify how quickly the anomaly has to be mitigated. Advantageously, predictive time series analysis enables prevention of a catastrophic disaster in the technical installation. The method further comprises a step of displaying the predictive time series analysis in conjunction with the representative view of the at least one portion of the technical installation. The predictive time series analysis and the representative view of the technical installation may be displayed, for example, on the display unit of the wearable device of the entity. The predictive time series analysis may be displayed, for example, as a hologram. Advantageously, the predictive time series analysis along with the representative view of the technical installation enables creation of situational awareness on the technical installation. Therefore, the entity is cognizant of events that may take place in the technical installation. Thus, the invention makes the entity capable of taking quick and informed decisions to maintain the technical installation. Yet another advantage of the invention is that the entity receives information about the technical installation on-the-go. The need to navigate to a certain location to identify an issue and obtain more data on the detected event is eliminated.

According to an embodiment of the invention, the method further comprises performing at least one mitigation action to address the detected event in the portion of the technical installation based on the predictive time series analysis. A mitigation action is a step or a process implemented to reduce or eradicate risk to human life and property from one or more events. Based on the predictive time series analysis, one or more mitigation actions may be identified and performed so as to address the detected event. The advantage of the invention is that the detected event is resolved by implementation of at least one mitigation action. The performance of the mitigation action enables prevention of catastrophic disasters in the technical installation, thereby maintaining safety of life and property. Yet another advantage of the invention is that performance of mitigation action ensures effective and efficient maintenance of the technical installation. Therefore, breakdown of the technical installation can be avoided and reduced.

According to an embodiment of the invention, in detecting the event in the portion of the technical installation, the method includes receiving sensor data from one or more sensor units disposed in the technical installation. Such sensor data is associated with the at least one portion of the technical installation. The sensor units disposed in the technical installation are capable of capturing parameter values associated with the working of the

technical installation. The sensor units may be, for example, sensors adapted to detect pressure, temperature, flow and control parameters associated with the technical installation. The method further includes analyzing the sensor data and detecting the event associated with the portion of the technical installation. The sensor data is analyzed to identify an anomaly in the functioning of the technical installation. The advantage of the invention is that the data pertaining to the technical installation is constantly monitored and a distortion in the parameter values is identified quickly.

According to another embodiment of the invention, in generating the predictive time series analysis, the method includes identifying one or more parameters associated with the functioning of the at least one portion of the technical installation. The parameters pertaining to the functioning of the technical installation may be, but not limited to, pressure, temperature, flow and control. The method further includes identifying a threshold value for each of the one or more parameters. The threshold value determines the permissible limits within which the values of the parameters may lie for effective functioning of the unit of the technical installation. Real-time values of the one or more parameters are received from one or sensors that are disposed in the at least one portion of the technical installation. As the one or more units within the technical installation function, real-time values associated with the parameters are recorded by the one or more sensors. Such real-time values may also be alternatively referred to as sensor data. Each of the values recorded include a time stamp. A time stamp enables clear identification of parameter values at a given point in time. Therefore, this further enables determination of a time duration within which the detected event may have to be addressed and resolved. A predictive time series analysis is generated using the received values. The predictive time series analysis is associated with the detected event. Advantageously, the predictive time series analysis enables determination of how the detected event may progress over a period of time. The predictive time series analysis provides a comprehensive understanding on the time period available to mitigate the detected event. Yet another advantage of the invention is that the predictive time series analysis provides cognition regarding gravity of the detected event.

According to yet another embodiment of the invention, generating the predictive time series analysis includes determining one or more probable estimate values of one or more parameters based on the real-time data received from one or more sensors disposed in the technical installation. Such determination may be made using a prediction model. The prediction model may use the real-time parameter values to estimate how the values may change over a given period of time. The probable estimate values are distributed at regu-

lar intervals of time to generate a predictive time series analysis of the parameter values. The advantage of the invention is that a situational awareness associated with the at least one portion of the technical installation is created.

5 According to another embodiment of the invention, in performing the mitigation action to address the detected event, the method includes detecting an anomaly associated with the event based on the predictive time series analysis of the received values. The predic-
10 tive time series analysis enables identification of parameters which may deviate from a certain standard. Deviation of one or more parameters from the standard may indicate an event in the functioning of the technical installation. The detected event may be an anomaly in the functioning of the technical installation. The sensor data may provide in-
15 formation on the functioning of the portion of the technical installation. Based on the predictive analysis of the sensor data, any possible occurrence of an anomaly in the function-
ing of the technical installation may be detected. Advantageously, the predictive time se-
ries analysis provides for early detection of anomaly in the technical installation. The
20 method further comprises determining a mitigation action to resolve the detected anomaly. On detection of the anomaly in the functioning of the technical installation, it may be es-
sential to determine one or more mitigation actions to resolve the detected anomaly. A
mitigation action may be an action taken specific to the anomaly so as to reduce or elimi-
nate risk to property and/or human life. The mitigation action is performed in the at least
25 one portion of the technical installation so as to resolve the detected anomaly. The ad-
vantage of the invention is that the anomaly in the technical installation is detected early
and therefore, the anomaly can be mitigated without causing loss to property and life. Yet
another advantage of the invention is that on detection of the anomaly, an appropriate
30 mitigation action is determined and performed in the portion of the technical installation.
Therefore, the entity is made aware of the mitigation actions available to resolve the de-
tected anomaly. Thereafter, the mitigation action is also performed in the technical instal-
lation to rectify the detected anomaly.

30 According to yet another embodiment of the method, in determining the mitigation action, the method includes analyzing an event log that may correspond to the at least one por-
tion of the technical installation. The events occurring in the at least one portion of the
technical installation may be recorded in the form of an event log. An event log may be a
35 record of any occurrence in the technical installation that may be useful in understanding
activities in the technical installation. The occurrences that may be recorded in the event
log may include, but is not limited to errors, warnings, and informational messages. The
event log may include a record of the time and date of occurrence of the event, type of

event, source of the event and/or an event ID. Analysis of the event log enables determination of the nature and cause of the detected event. The event may be reconstructed based on the event log so as to determine the cause of malfunction in the portion of the technical installation. The events in an event log may be stored chronologically and may
5 be replayed in the same order to reconstruct the event, for example, in the form of a process history. In an embodiment, the events may be reconstructed and represented on a map. For example, a map designer well known in the state of the art may be used to generate a map on which the event may be reconstructed. The map may be, for example, but not limited to, Cartesian map, timeline based map or a process model map. Based on the
10 reconstructed event, one or more mitigation actions are identified. Such one or more mitigation actions may have been performed previously in the technical installation to mitigate similar events. A most appropriate mitigation action may be determined from the one or more previously implemented mitigation actions, to resolve the detected event. Alternatively, if no previously implemented mitigation actions are identified for the detected event,
15 a new mitigation action that may resolve the detected event may be determined by identifying steps that may be taken to overcome the anomaly and reduce the impact of the malfunction of the technical installation. Advantageously, determination of the most appropriate mitigation action ensures effective maintenance of the technical installation. The most appropriate mitigation action may entail, for example, reduced risk of long term damage to
20 the technical installation, efficient working of the technical installation, and/or quicker resolution of the anomaly.

According to an embodiment of the invention, in determining the most appropriate mitigation action, the method includes generating a predictive time series analysis for each of
25 the identified mitigation actions. Predictive time series analysis of each of the mitigation action may be generated using a prediction model. The prediction model may determine how one or more parameters essential for the functioning of at least one portion of the technical installation may change on implementation of the mitigation action. The outcome of each of the mitigation actions may be determined by analysis of the predictive time series data generated for each of the mitigation actions. The predictive time series analysis
30 of the identified mitigation actions enables determination of possible repercussions of implementation of the mitigation action. There may be several approaches for resolving an anomaly. However, not all the approaches may be the best ones. For example, implementation of one of the mitigation actions may be dependent on efficient functioning of a unit
35 in the technical installation. However, if the said unit is non-functional or is under maintenance, implementation of the corresponding mitigation action may not resolve the anomaly detected in the technical installation. Implementation of such mitigation action may

cause further damage to the technical installation. Therefore, determining the outcome of a mitigation action is essential so as to take an informed decision for resolving the anomaly. The mitigation action with the most appropriate outcome, in comparison with the outcomes of all the identified mitigation actions, is determined to resolve the anomaly in the technical installation. Advantageously, the determination of the most appropriate mitigation action enables efficient and quick resolution of the detected anomaly. Determination of the most appropriate mitigation action prevents expenditure of time in implementing actions that may not resolve the detected anomaly. Yet another advantage is that risk in implementing a certain mitigation action is identified before such implementation and therefore, loss to property and life is avoided. An informed decision process is enabled thereby creating effective situational awareness of the technical installation.

According to yet another embodiment of the invention, the method further comprises establishing a communication channel between the at least one wearable device and the other wearable devices of the one or more entities associated with the technical installation. A communication channel is a mode or a transmission medium used for transfer of information between one or more entities, from one location to another. The communication channel established between the wearable devices enables transfer of information from one entity to another.

According to an embodiment of the invention, the method further comprises identifying an appropriate escalation matrix associated with the detected anomaly. The escalation matrix may include at least one entity to be reported regarding the detected anomaly. The escalation matrix may be identified, for example, based on the one or more unit in the at least one portion of the technical installation where the anomaly is detected. Alternatively, the escalation matrix may also be identified based on the nature of the detected anomaly. The escalation matrix includes at least one entity who may be responsible for the maintenance and management of the technical installation. The at least one entity may also be a person who has an expertise in a domain corresponding to the at least one portion of the technical installation and is capable of resolving the detected anomaly in the technical installation. In an embodiment, the method further comprises displaying the mitigation action and the corresponding escalation matrix on the wearable device. At least one entity associated with the wearable device may view the escalation matrix in conjunction with the mitigation actions. Such at least one entity may further share the identified mitigation actions to the wearable device of the at least one entity included in the escalation matrix. Advantageously, identification of the escalation matrix enables identification of one or more entities to be informed about the detected anomaly. Therefore, obtaining an expert

view on the nature of the anomaly and on the mitigation action to resolve such anomaly is made possible by the invention. Identification of the escalation matrix and sharing the mitigation actions with the entity in the escalation matrix facilitates uniform information access across one or more relevant entities. This ensures efficient maintenance of the technical installation.

According to another embodiment of the invention, a conference session may be set up between the connected wearable devices via the communication channel. The conference session enables one or more entities associated with the connected wearable devices to interact with each other. The conference session may be, for example a telephonic call between the entities associated with the connected wearable devices. Therefore, the one or more entities may participate in the call either via voice and audio or only via audio. In an embodiment, the conference session may be secured by a security code or a personal identification number (PIN) such that only authorized entities may participate in the session. The conference session enables participation of one or more entities present in different locations. Therefore, one or more entities may provide their inputs remotely. The conference session further saves time and effort to connect to more than one entity at the same time, thereby providing an interactive environment for effective resolution of issues.

According to yet another embodiment of the invention, the method further comprises sharing the representative view and the predictive time series analysis of the portion of the technical installation with the connected wearable devices of the one or more entities via the communication channel and receiving an input from a first entity of the one or more entities through a user interface of the wearable device of the first entity. In an embodiment, the established communication channel may be configured to receive one or more inputs from one entity and transmit such input to one or more other entities. Such transmission of one or more inputs may be performed in real-time. A user interface to receive inputs from the one or more entities may also be displayed on the display unit of the wearable device in conjunction with the multi-dimensional view and the predictive time series analysis. In the embodiment, one of the one or more entities may provide an input using the user interface. Such input may be capable of generating additional content, such as a change in the multi-dimensional view of the technical installation. For example, an input from one of the entities may render a blown-up view of the technical installation such that one or more internal units of the technical installation may be visualized. The communication channel may be capable of receiving such input from the entity and transmitting the input to the other entities in real-time to the connected wearable devices of the remaining entities. The method further comprises receiving an input from a second entity of

the one or more entities through the user interface of the wearable device of the second entity, in response to the input of the first entity. In an embodiment, the communication channel may be adapted to receive and transmit input from only one entity at a given point in time. Therefore, clarity in the inputs from the entities is maintained.

5

According to an embodiment of the invention, the method includes generating an alert on the at least one wearable device when an event associated with the portion of the technical installation is detected. The alert may be generated as, for example, but not limited to, a notification on the display unit of the wearable device. The notification may be displayed on the display unit of the wearable device such that it occupies a major portion of the display area. Such area occupied by the notification may be increased or decreased depending upon the criticality of the information to be conveyed. In an embodiment, the notification may be indicated on the display unit using a different color to draw the attention of the entity associated with the wearable device. In another embodiment, the notification may be generated in conjunction with a sound. In yet another embodiment, the alert may also include a pulse vibration in the wearable device, such that the wearable device vibrates in pulses when an alert is generated. Advantageously, the alert facilitates creation of situational awareness about the events occurring in different portions of the technical installation. Therefore, any event, critical or otherwise, may be addressed by the one or more entities such that efficient and quick resolution to the problem is achieved.

10
15
20

The invention also relates to a system for managing a technical installation. The system comprises one or more processing units. In an embodiment, the system may comprise an interface capable of receiving data from a technical database. The technical database may contain data related to one or more parameters associated with the at least one portion of the technical installation. In an embodiment, the technical database may be present in a cloud environment. The interface may be, for example, data bus which is configured to receive data from the technical database. The system further comprises one or more memory units coupled to the processing units. The one or more memory units include a situational awareness based management module which is configured to perform a method according to claims 1 to 13.

25
30

According to an embodiment of the invention, in managing the technical installation, the situational awareness based management module, when executed by the processing unit, is configured to detect an event associated with a portion of the technical installation based on sensor data associated with the portion of the technical installation. One or more sensors may be disposed in at least a portion of the technical installation. The one or

35

more sensors may be adapted to receive one or more values associated with the technical installation which may correspond to the functioning of the technical installation. Such values may be related to one or more parameters, for example, but not limited to pressure, temperature, flow and control. These parameters are monitored to determine the functioning of the technical installation. Based on the parameter values obtained from the sensors, an event may be detected in the portion of the technical installation. These one or more parameters obtained from one or more sensors may be stored in the technical database. The event may be, for example, an anomaly or abnormality in the working of the technical installation. The management module is further configured to render a representative view of the portion of the technical installation on a wearable device. The representative view may display information associated with the detected event in conjunction with the multi-dimensional view of the portion of the technical installation. According to an embodiment of the invention, the representative view of the technical installation may be a holographic view. A hologram is a photographic recording of a light field that is used to display a multi-dimensional image of the holographed subject. In an embodiment of the invention, a hologram of the portion of the technical installation is generated using methods well-known in the art. The holographic view of the portion of the technical installation is coupled with information pertaining to the detected event. For example, if a unit in the portion of the technical installation is malfunctioning, information related to such malfunctioning unit may be overlaid on the multi-dimensional view of the technical installation. The information may be, for example, one or more parameters associated with the functioning of the unit in the technical installation. The values for each of the parameters may be displayed in conjunction with the representative view of the portion of the technical installation. This enables an entity to determine the cause of the malfunction of the unit. In another embodiment of the invention, the malfunctioning unit may be indicated, for example, with a different color or as a hologram in motion. The hologram in motion may, for example, be a hologram depicted with a pulsating motion such that the malfunctioning unit of the technical installation appears to pulsate. The advantage of rendering a representative view is that the detected event in the portion of the technical installation can be located easily. This enables identification of the malfunctioning unit within the technical installation efficiently.

The management module is further configured to generate a predictive time series analysis of the sensor data associated with the detected event. A predictive time series analysis refers to determination of how an event would progress over a period of time. Sensor data refers to data associated with the technical installation and may include values associated with one or more parameters related to the functioning of the technical installation. The

predictive analysis is based on a time series analysis. The values associated with the parameters of the unit have a threshold. The threshold determines the permissible limits within which the values of the parameters may lie for effective functioning of the unit of the technical installation. The management module may comprise a predictive model which
5 may be configured to divide the limits based on time. The divided limits are used produce a predictive time series analysis based on the sensor data associated with the detected event. The predictive time series analysis advantageously enables the entity to determine how the event would progress over a period of time. Predictive time series analysis also allows the entity to identify how quickly the anomaly has to be mitigated. Advantageously,
10 predictive time series analysis enables prevention of a catastrophic disaster in the technical installation. The management module is further configured to display the predictive time series analysis in conjunction with the representative view of the at least one portion of the technical installation. The predictive time series analysis and the representative view of the technical installation may be displayed, for example, on the display unit of the
15 wearable device of the entity. The predictive time series analysis may be displayed, for example, as a hologram. Advantageously, the predictive time series analysis along with the representative view of the technical installation enables creation of situational awareness on the technical installation. Therefore, the entity is cognizant of events taking place in the technical installation. Thus, the invention makes the entity capable of taking quick
20 and informed decisions to maintain the technical installation. Yet another advantage of the invention is that the entity receives information about the technical installation on-the-go. The need to navigate to a certain location to identify an issue and obtain more data on the detected event is eliminated.

25 According to an embodiment of the invention, the management module is further configured to perform at least one mitigation action to address the detected event in the portion of the technical installation based on the predictive time series analysis. A mitigation action is a step or a process implemented to reduce or eradicate risk to human life and property from one or more events. Based on the predictive time series analysis, one or
30 more mitigation actions may be identified and performed so as to address the detected event. The advantage of the invention is that the detected event is resolved by implementation of at least one mitigation action. The performance of the mitigation action enables prevention of catastrophic disasters on and in the technical installation, thereby maintaining safety of life and property. Yet another advantage of the invention is that performance
35 of mitigation action ensures effective and efficient maintenance of the technical installation.

According to an embodiment of the invention, in detecting the event in the portion of the technical installation, the management module is configured to receive sensor data from one or more sensor units disposed in the technical installation. Such sensor data may be obtained from the technical database. Such sensor data is associated with the at least
5 one portion of the technical installation. The sensor units disposed in the technical installation are capable of capturing parameter values associated with the working of the technical installation. The sensor units may be, for example, sensors adapted to detect pressure, temperature, flow and control parameters associated with the technical installation. The management module is further configured to analyze the sensor data and detect the
10 event associated with the portion of the technical installation. The sensor data is analyzed to identify an anomaly in the functioning of the technical installation. The advantage of the invention is that the data pertaining to the technical installation is constantly monitored and a distortion in the parameter values is identified quickly.

15 According to another embodiment of the invention, in generating the predictive time series analysis, the management module is configured to identify one or more parameters associated with the functioning of the at least one portion of the technical installation. The parameters pertaining to the functioning of the technical installation may be, but not limited to, pressure, temperature, flow and control. The management module is further configured
20 to identify a threshold value for each of the one or more parameters. The threshold value determines the permissible limits within which the values of the parameters may lie for effective functioning of the unit of the technical installation. Real-time values of the one or more parameters are received from one or sensors that are disposed in the at least one
25 portion of the technical installation. As the one or more units within the technical installation function, real-time values associated with the parameters are recorded by the one or more sensors. Such real-time values may also be alternatively referred to as sensor data. Each of the values recorded include a time stamp, indicating the parameter value at a certain time period. A time stamp enables clear identification of parameter values at a given point in time. Therefore, this further enables determination of a time duration within
30 which the detected event would have to be addressed and resolved. A predictive time series analysis is generated using the received values. The predictive time series analysis is associated with the detected event. Advantageously, the predictive time series analysis enables determination of how the detected event would progress over a period of time. The predictive time series analysis provides a comprehensive understanding on the time
35 period available to mitigate the detected event. Yet another advantage of the invention is that the predictive time series analysis provides cognition regarding gravity of the detected event.

According to yet another embodiment of the invention, in generating the predictive time series analysis, the management module is configured to determine one or more probable estimate values of one or more parameters based on the real-time data received from one or more sensors disposed in the technical installation. Such determination may be made using the prediction model. The prediction model may use the real-time parameter values to estimate how the values may change over a given period of time. The probable estimate values are distributed at regular intervals of time to generate a predictive time series analysis of the parameter values. The advantage of the invention is that a situational awareness associated with the at least one portion of the technical installation is created.

According to another embodiment of the invention, in performing the mitigation action to address the detected event, the management module is configured to detect an anomaly associated with the event based on the predictive time series analysis of the received values. The predictive time series analysis enables identification of parameters which may deviate from a certain standard. Deviation of one or more parameters from the standard may indicate an event in the functioning of the technical installation. The detected event may be an anomaly in the functioning of the technical installation. The sensor data may provide information on the functioning of the portion of the technical installation. Based on the predictive analysis of the sensor data, any possible occurrence of an anomaly in the functioning of the technical installation may be detected. Advantageously, the predictive time series analysis provides for early detection of anomaly in the technical installation. The management module is further configured to determine a mitigation action to resolve the detected anomaly. On detection of the anomaly in the functioning of the technical installation, it may be essential to determine one or more mitigation actions to resolve the detected anomaly. A mitigation action may be an action taken specific to the anomaly so as to reduce or eliminate risk to property and/or human life. The mitigation action is performed in the at least one portion of the technical installation so as to resolve the detected anomaly. The advantage of the invention is that the anomaly in the technical installation is detected early and therefore, the anomaly can be mitigated without causing loss to property and life. Yet another advantage of the invention is that on detection of the anomaly, an appropriate mitigation action is determined and performed in the portion of the technical installation. Therefore, the entity is made aware of the mitigation actions available to resolve the detected anomaly. Thereafter, the mitigation action is also performed in the technical installation to rectify the detected anomaly.

According to yet another embodiment of the method, in determining the mitigation action, the management module is configured to analyze an event log that may correspond to the at least one portion of the technical installation. The events occurring in the at least one portion of the technical installation may be recorded in the form of an event log. An event log may be a record of any occurrence in the technical installation that may be useful in understanding activities in the technical installation. The occurrences that may be recorded in the event log may include, but is not limited to errors, warnings, and informational messages. The event log may include a record of the time and date of occurrence of the event, type of event, source of the event and/or an event ID. Analysis event log enables determination of the nature and cause of the detected event. The event may be reconstructed based on the event log so as to determine the cause of malfunction in the portion of the technical installation. The events in an event log may be stored chronologically and may be replayed in the same order to reconstruct the event, for example, in the form of a process history. The events may be reconstructed and represented on a map. For example, a map designer well known in the state of the art may be used to generate a map on which the event may be reconstructed. The map may be, for example, but not limited to, Cartesian map, timeline based map or a process model map. Based on the reconstructed event, one or more mitigation actions are identified. Such one or more mitigation actions may have been performed previously in the technical installation to mitigate similar events in the technical installation. A most appropriate mitigation action may be determined from the one or more previously implemented mitigation actions, to resolve the detected event. Alternatively, if no previously implemented mitigation actions are identified for the detected event, a new mitigation action that may resolve the detected event may be determined by identifying steps that may be taken to overcome the anomaly and reduce the impact of the malfunction of the technical installation. Advantageously, determination of the most appropriate mitigation action ensures effective maintenance of the technical installation. The most appropriate mitigation action may entail, for example, reduced risk of long term damage to the technical installation, efficient working of the technical installation, and/or quicker resolution of the anomaly.

According to an embodiment of the invention, in determining the most appropriate mitigation action, the management module is configured to generate a predictive time series analysis for each of the identified mitigation actions. Predictive time series analysis of each of the mitigation action may be generated using a prediction model. The prediction model may determine how one or more parameters essential for the functioning of at least one portion of the technical installation may change on implementation of the mitigation action. The outcome of each of the mitigation actions may be determined by analysis of

the predictive time series data generated for each of the mitigation actions. The predictive time series analysis of the identified mitigation actions enables determination of possible repercussions of implementation of the mitigation action. There may be several approaches for resolving an anomaly. However, not all the approaches may be the best ones. For example, implementation of one of the mitigation actions may be dependent on efficient functioning of a related unit in the technical installation. However, if the said unit is non-functional or is under maintenance, implementation of the corresponding mitigation action may not resolve the anomaly detected in the technical installation. Such implementation of mitigation action may cause further damage to the technical installation. Therefore, determining the outcome of a mitigation action is essential so as to take an informed decision for resolving the anomaly. The mitigation action with the most appropriate outcome, in comparison with the outcomes of all the identified mitigation actions, is determined to resolve the anomaly in the technical installation. Advantageously, the determination of the most appropriate mitigation action enables efficient and quick resolution of the detected anomaly. Determination of the most appropriate mitigation action prevents expenditure of time in implementing actions that may not resolve the detected anomaly. Yet another advantage is that risk in implementing a certain mitigation action is identified before such implementation and therefore, loss to property and life is avoided. An informed decision process is enabled thereby creating effective situational awareness of the technical installation.

According to yet another embodiment of the invention, the management module is further configured to establish a communication channel between the at least one wearable device and the other wearable devices of the one or more entities associated with the technical installation. A communication channel is a mode or a transmission medium used for transfer of information between one or more entities, from one location to another. The communication channel established between the wearable devices enables transfer of information from one entity to another.

According to an embodiment of the invention, the management module is configured to identify an appropriate escalation matrix associated with the detected anomaly. The escalation matrix may include at least one entity to be reported regarding the detected anomaly. The escalation matrix may be identified, for example, based on the one or more unit in the at least one portion of the technical installation where the anomaly is detected. Alternatively, the escalation matrix may also be identified based on the nature of the detected anomaly. The escalation matrix includes at least one entity who may be responsible for the maintenance and management of the technical installation. The at least one entity

may also be a person who has an expertise in a domain corresponding to the at least one portion of the technical installation and is capable of resolving the detected anomaly in the technical installation. In an embodiment, the management module is further configured to display the mitigation action and the corresponding escalation matrix on the display unit of the wearable device. At least one entity associated with the wearable device may view the escalation matrix in conjunction with the mitigation actions. Such at least one entity may further share the identified mitigation actions to the wearable device of the at least one entity included in the escalation matrix. Advantageously, identification of the escalation matrix enables identification of one or more entities to be informed about the detected anomaly. Therefore, obtaining an expert view on the nature of the anomaly and on the mitigation action to resolve such anomaly is made possible by the invention. Identification of the escalation matrix and sharing the mitigation actions with the entity in the escalation matrix facilitates uniform information access across one or more relevant entities. This ensures efficient maintenance of the technical installation.

According to another embodiment of the invention, the management module may also be configured to set up a conference session between the connected wearable devices via the communication channel. The conference session enables one or more entities associated with the connected wearable devices to interact with each other. The conference session may be, for example, a telephonic call between the entities associated with the connected wearable devices. Therefore, the one or more entities may participate in the call either via voice and audio or only via audio. In an embodiment, the conference session may be secured by a security code or a personal identification number (PIN) such that only authorized entities may participate in the session. The conference session enables participation of one or more entities present in different locations. Therefore, one or more entities may provide their inputs remotely. The conference session further saves time and effort to connect to more than one entity at the same time, thereby providing an interactive environment for effective resolution of issues.

According to yet another embodiment of the invention, the management module is further configured to share the representative view and the predictive time series analysis of the portion of the technical installation with the connected wearable devices of the one or more entities via the communication channel and receiving an input from a first entity of the one or more entities through a user interface of the wearable device of the first entity. In an embodiment, the established communication channel may be configured to receive one or more inputs from one entity and transmit such input to one or more other entities. Such transmission of one or more inputs may be performed in real-time. A user interface

to receive inputs from the one or more entities may also be displayed on the display unit of the wearable device in conjunction with the multi-dimensional view and the predictive time series analysis. In the embodiment, one of the one or more entities may provide an input using the user interface. Such input may be capable of generating additional content, such as a change in the multi-dimensional view of the technical installation. For example, an input from one of the entities may render a blown-up view of the technical installation such that one or more internal units of the technical installation may be visualized. The communication channel may be capable of receiving such input from the entity and transmitting the input to the other entities in real-time to the connected wearable devices of the remaining entities. The management module may be further configured to receive an input from a second entity of the one or more entities through the user interface of the wearable device of the second entity, in response to the input of the first entity. In an embodiment, the communication channel may be adapted to receive and transmit input from only one entity at a given point in time. Therefore, clarity in the inputs from the entities is maintained.

According to an embodiment of the invention, the management module may be configured to generate an alert on the at least one wearable device when an event associated with the portion of the technical installation is detected. The alert may be generated as, for example, but not limited to, a notification on the display unit of the wearable device. The notification may be displayed on the display unit of the wearable device such that it occupies a major portion of the display area. Such area occupied by the notification may be more or less depending upon the criticality of the information to be conveyed. In an embodiment, the notification may be indicated on the display unit using a different color to draw the attention of the entity associated with the wearable device. In another embodiment, the notification may be generated in conjunction with a sound. In yet another embodiment, the alert may also include a pulse vibration in the wearable device, such that the wearable device vibrates in pulses when an alert is generated. Advantageously, the alert facilitates creation of situational awareness about the events occurring in different portions of the technical installation. Therefore, any event, critical or otherwise, may be addressed by the one or more entities such that efficient and quick resolution to the problem is achieved.

The invention also relates to a system comprising one or more servers remotely located from a technical installation. The system further comprises one or more sensors communicatively coupled to the one or more servers and one or more wearable devices communicatively coupled to the one or more servers. The one or more servers comprise comput-

er readable instructions, which when executed by the one or more servers cause the one or more servers to perform the method according to claims 1 to 13.

5 The invention relates in one aspect to a computer program product comprising a computer program, the computer program being loadable into a storage unit of a system, including machine readable instructions which when executed by a processing unit causes the processing unit to perform a method according to an aspect of the invention.

10 The realization of the invention by a computer program product and/or a computer-readable medium has the advantage that already existing management systems can be easily adopted by software updates in order to work as proposed by the invention.

15 The computer program product can be, for example, a computer program or comprise another element apart from the computer program. This other element can be hardware, for example a memory device, on which the computer program is stored, a hardware key for using the computer program and the like, and/or software, for example a documentation or a software key for using the computer program.

20 The present invention is further described hereinafter with reference to illustrated embodiments shown in the accompanying drawings, in which:

FIG 1 illustrates a block diagram of a client-server architecture which provides geometric modeling of components representing different parts of a real world object, according to an embodiment.

25 FIG 2 illustrates a block diagram of a system in which an embodiment of a method of managing a technical installation can be implemented.

FIG 3 illustrates a flow chart of an embodiment of a method of managing a technical installation.

30 FIG 4 illustrates a flowchart of an embodiment of a method of detecting an event in a portion of the technical installation.

FIG 5 illustrates a flowchart of an embodiment of a method of generating a predictive time series analysis.

FIG 6 illustrates a flowchart of an embodiment of a method of performing a mitigation action to address the event.

35 FIG 7 illustrates a flowchart of an embodiment of a method of determining mitigation action to resolve the detected anomaly.

FIG 8 illustrates a flowchart of an embodiment of a method of determining the most appropriate mitigation action for resolving the detected anomaly.

FIG 9 illustrates a flowchart of an additional embodiment of a method of managing a technical installation.

5 FIG 10 illustrates a flowchart of an embodiment of a method, according to the invention.

FIG 11 illustrates an embodiment of a representative view of a technical installation, according to the invention.

FIG 12 illustrates an embodiment of a graphical user interface in conjunction with a representative view of a portion of the technical installation.

10 FIG 13 illustrates an embodiment of a graphical user interface providing a pictorial representation of an alert generated on a display unit of a wearable device.

Hereinafter, embodiments for carrying out the present invention are described in detail.

The various embodiments are described with reference to the drawings, wherein like reference numerals are used to refer to like elements throughout. In the following description, for purpose of explanation, numerous specific details are set forth in order to provide a thorough understanding of one or more embodiments. It may be evident that such em-
15 bodiments may be practiced without these specific details.

20 FIG 1 provides an illustration of a block diagram of a client-server architecture that is a geometric modelling of components representing different parts of real-world objects, according to an embodiment. The client-server architecture 100 includes a server 101, one or more client devices 107a-c, and a technical installation 108. The client device 107a-c may be, for example, a wearable device such as a head mounted display. The one or
25 more client devices 107a-c and the technical installation 108 are connected to the server 101 via a network 105, for example, local area network (LAN), wide area network (WAN), WiFi, etc. In one embodiment, the server 101 is deployed in a cloud computing environment. As used herein, "cloud computing environment" refers to a processing environment comprising configurable computing physical and logical resources, for example, networks,
30 servers, storage, applications, services, etc., and data distributed over the network 105, for example, the internet. The cloud computing environment provides on-demand network access to a shared pool of the configurable computing physical and logical resources. The server 101 may include a technical database 102 that comprises sensor data obtained
35 from one or more sensors deployed in the technical installation 108. The technical database 102 may also include event logs of the technical installation 108 and values associated with one or more parameters associated with the functioning of the technical installation 108. The server 101 may further include a situational awareness based management

module 103 that is configured to manage the technical installation 108. The server 101 may include an interface 104 that receives data, for example, sensor data from one or more sensors and transfers the sensor data to the technical database 102. Additionally, the interface 104 may also communicate with the client devices 107a-c and the technical installation 108 via the network 105.

The client device 107a-c is used by an entity to access data associated with the technical installation 108 to manage the technical installation 108. The data on the server 101 can be accessed by the entity via a graphical user interface of an end user web application.

FIG 2 is a block diagram of a system 101 in which an embodiment can be implemented, for example, as a system to manage a technical installation, configured to perform the processes as described therein. It is appreciated that the server 101 is an exemplary implementation of the system in FIG 1. In an embodiment, the system 101 may be a maintenance management system for the technical installation 108. In FIG 2, the system 101 comprises a memory 201, a processing unit 202, a storage unit 203, an input unit 204, an output unit 205, a network interface 104 and a standard interface or bus 206. The system 101 can be a (personal) computer, a workstation, a virtual machine running on host hardware, a microcontroller, or an integrated circuit. As an alternative, the system 101 can be a real or a virtual group of computers (the technical term for a real group of computers is "cluster", the technical term for a virtual group of computers is "cloud").

The processing unit 202, as used herein, means any type of computational circuit, such as, but not limited to, a microprocessor, microcontroller, complex instruction set computing microprocessor, reduced instruction set computing microprocessor, very long instruction word microprocessor, explicitly parallel instruction computing microprocessor, graphics processor, digital signal processor, or any other type of processing circuit. The processing unit 202 may also include embedded controllers, such as generic or programmable logic devices or arrays, application specific integrated circuits, single-chip computers, and the like. In general, a processing unit 202 can comprise hardware elements and software elements. The processing unit 202 can be configured for multithreading, i.e. the processing unit 202 can host different calculation processes at the same time, executing the either in parallel or switching between active and passive calculation processes.

The memory 201 may be volatile memory and non-volatile memory. The memory 201 may be coupled for communication with the processing unit 202. The processing unit 202 may execute instructions and/or code stored in the memory 201. A variety of computer-

readable storage media may be stored in and accessed from the memory 201 . The memory 201 may include any suitable elements for storing data and machine-readable instructions, such as read only memory, random access memory, erasable programmable read only memory, electrically erasable programmable read only memory, a hard drive, a removable media drive for handling compact disks, digital video disks, diskettes, magnetic tape cartridges, memory cards, and the like. In the present embodiment, the memory 201 includes a situational awareness based management module 103 stored in the form of machine-readable instructions on any of the above-mentioned storage media and may be in communication to and executed by processing unit 202. When executed by the processing unit 202, the management module 103 causes the processing unit 202 to manage a technical installation 108. Method steps executed by the processing unit 202 to achieve the abovementioned functionality are elaborated upon in detail in FIG 3-10.

The storage unit 203 may be a non-transitory storage medium which stores a technical database 102. The technical database 102 is a repository of information related to the technical installation 108. The input unit 204 may include input means such as keypad, touch-sensitive display, camera (such as a camera receiving gesture-based inputs), etc. capable of receiving input signal. The bus 206 acts as interconnect between the processing unit 202, the memory 201 , the storage unit 203, the communication interface 104 the input unit 204 and the output unit 205.

Those of ordinary skilled in the art will appreciate that the hardware depicted in FIG 2 may vary for particular implementations. For example, other peripheral devices such as an optical disk drive and the like, Local Area Network (LAN)/ Wide Area Network (WAN)/ Wireless (e.g., Wi-Fi) adapter, graphics adapter, disk controller, input/output (I/O) adapter also may be used in addition or in place of the hardware depicted. The depicted example is provided for the purpose of explanation only and is not meant to imply architectural limitations with respect to the present disclosure.

A system 101 in accordance with an embodiment of the present disclosure includes an operating system employing a graphical user interface. The operating system permits multiple display windows to be presented in the graphical user interface simultaneously with each display window providing an interface to a different application or to a different instance of the same application. A cursor in the graphical user interface may be manipulated by an entity through a pointing device or touch based gestures or hand gestures. The position of the cursor may be changed and/or an event such as clicking a mouse button, generated to actuate a desired response.

One of various commercial operating systems, such as a version of Microsoft Windows™, a product of Microsoft Corporation located in Redmond, Washington may be employed if suitably modified. The operating system is modified or created in accordance with the present disclosure as described.

Disclosed embodiments provide systems and methods for managing a technical installation. In particular, the systems and methods may perform maintenance of at least a portion of the technical installation.

FIG 3 illustrates a flowchart of an embodiment of a method 300 of managing a technical installation 108. Such technical installation 108 may be remotely located, for example, in an offshore location. The technical installation 108 may be a complex industrial set-up with a plurality of units. Each unit of the plurality of units may function individually but in collaboration with other units so as to ensure efficient functioning of the technical installation 108. Therefore, breakdown of one of the units may lead to breakdown of the entire technical installation 108. Thus, awareness of the functioning of each unit is of utmost importance. The invention may be paramount in, for example, but not limited to, a maintenance management system 101. The maintenance management system 101 may be capable of performing maintenance activities in the technical installation 108. Such maintenance management system may be remotely located from the technical installation 108. In managing the technical installation, the method 300 includes a step 301 of detecting an event associated with a portion of the technical installation 108. An event may be an occurrence deviating from a standard, which requires attention of the entity for resolution. In an embodiment of the method, the event may be detected based on sensor data received from one or more sensors in the technical installation 108. The technical installation 108 may have one or more sensors to monitor one or more parameters associated with the functioning of the technical installation 108. The one or more parameters may be, for example, pressure, temperature and flow characteristics associated with at least a portion of the technical installation 108. An embodiment of a method of detecting the event in the technical installation 108 is illustrated in a flowchart in FIG 4. At step 401, sensor data associated with the at least one portion of the technical installation is obtained from one or more sensors disposed in the technical installation. The one or more sensors are capable of interacting with the at least one portion of the technical installation to capture data associated with one or more parameters of the technical installation 108. At step 402, the sensor data is analysed to identify an abnormality in the parameter values. A threshold for each parameter is identified. Such threshold value may be pre-determined and may be

retrieved from the technical database 102. The parameter values are compared with the threshold value to determine if at least one parameter value deviates from the threshold value. At step 403, an event is detected based on the deviation identified between the captured parameter values and the threshold values. In an embodiment, an alert may be generated on at least one wearable device when the event is detected. The alert may be displayed on the display unit of the wearable device 107a-c as a notification 1301. In an alternate embodiment, the notification 1301 may be displayed in conjunction with the representative view 1101 of the technical installation 108. FIG 13 illustrates an embodiment of a graphical user interface 1200 providing a pictorial representation of an alert generated on a display unit of a wearable device. The notification 1301 may be displayed on the display unit of the wearable device 107a-c such that it occupies a major portion of the display area. Such area occupied by the notification 1301 may be increased or decreased depending upon the criticality of the information to be conveyed. Alternatively, the notification 1301 may be displayed in the peripheral area of the display unit of the wearable device such that the notification 1301 appears in the peripheral vision of the entity. In an embodiment, the notification 1301 may be indicated on the display unit using a different color to draw the attention of the entity associated with the wearable device 107a-c. In another embodiment, the notification 1301 may be generated in conjunction with a sound. In yet another embodiment, the alert may also include a pulse vibration in the wearable device, such that the wearable device 107a-c in pulses when an alert is generated.

On detecting the event in the portion of the technical installation 108, at step 302 of the method 300, a representative view 1101 of the portion is rendered on the wearable device 107a-c associated with the entity. In an embodiment, the representative view of the technical installation is a multi-dimensional holographic view. The holographic view 1101 of the technical installation enables the entity to understand the location of the event in the technical installation 108. The holographic view of the portion of the technical installation 108 may be a miniature replica of the original portion of the technical installation 108. FIG 11 illustrates an embodiment of the holographic view 1101 of the technical installation 108. In the embodiment, the holographic view 1101 of the technical installation 108 is rendered as a multi-dimensional augmented reality view. Therefore, the real-world environment of the entity is augmented with information related to the technical installation 108. The holographic view 1101 may be overlaid as constructive sensory information such that the entity continues to be aware of his real-world environment. Alternatively, the holographic view 1101 may also be rendered as a virtual image on the display unit of the wearable device 107a-c. In an embodiment, the holographic view 1101 of the technical installation 108 may also highlight the portion 1102 of the technical installation 108 where

the event is detected. Such portion of the technical installation 108 may be distinguished, for example, with a different colour, by outlining the portion of the technical installation 108, or as a hologram in motion. A hologram in motion may depict the hologram with a pulsating motion, thereby drawing the attention of the entity to the portion where the event is detected. The holographic view 1101 may depict information associated with the detected event in conjunction with the multi-dimensional view of the technical installation 108. Such information related to the detected event may include details associated with, but not limited to, the deviated parameters, criticality of the detected event and time of occurrence of the event. In an embodiment of the invention, the representative view 1101 of the technical installation 108 may remain stagnant such that the one or more entities may move around the representative view 1101. This enables the one or more entities to visualize the representative view 1101 from various directions and angles. Alternatively, the representative view 1101 may be turned in different directions and angles by one or more entities using, for example, hand gestures, or using a mouse drag.

At step 303 of method 300, a predictive time series analysis of the sensor data associated with the detected event is generated. A predictive time series analysis enables the entity to determine how the event may progress over a period of time. Therefore, the criticality of the detected event is presented to the entity. This further enables the entity to take an informed and quick decision to resolve the detected event. FIG 5 illustrates a flowchart of a method 500 of generating the predictive time series analysis of the sensor data. At step 501, one or more parameters associated with the functioning of the portion of the technical installation are identified. At step 502, a threshold value for each of the one or more parameters is identified. The threshold value enables determination of the limit within which the values associated with the one or more parameters may lie. The sensors disposed in the portion of the technical installation capture the parameter values in real-time. Such parameter values are received from the sensors, at step 503 through the interface 104. In an embodiment, the real-time sensor data may comprise a time stamp. The time stamp enables determination of the time of occurrence of the event in the portion of the technical installation. Based on the real-time values received from the sensors, one or more probable estimate values of the one or more parameters are determined at step 504 using a prediction model. Such probable estimate values are distributed at regular time intervals at step 505 to generate the predictive time series analysis of the values associated with the parameters, at step 506. Predictive time series analysis enables the maintenance management system 101 to determine how soon the maintenance of the technical installation 108 may be required. Therefore, timely maintenance of the technical installation 108 is facilitated.

At step 304 of the method 300, the predictive time series analysis is displayed on the wearable device in conjunction with the representative view of the portion of the technical installation. In an embodiment of the method, a communication channel 1100 may be established between at least one of the wearable devices 107a and other wearable devices 107b-c of the entities associated with the technical installation 108. The communication channel 1100 enables transfer of information from one wearable device 107a of one entity to other wearable devices 107b-c of the other entities. FIG 10 illustrates a flowchart of an embodiment of the method 1000. The representative view 1101 and the predictive time series analysis of the parameter values may be shared by one entity to another through the connected wearable devices 107a-c via the communication channel 1100, at step 1001. The one or more entities with whom the representative view 1101 and the predictive time series analysis are to be shared may be determined using an escalation matrix. FIG 9 illustrates an embodiment of a method 900 of sharing the representative view 1101 and the predictive time series analysis with the one or more entities in the escalation matrix. At step 901, an escalation matrix associated with the detected event or anomaly is identified. The escalation matrix may be identified based on the nature of the detected event. Alternatively, the escalation matrix may also be identified based on the entities responsible for the portion of the technical installation 108 where the event is detected. Such escalation matrix may include at least one entity to be reported about the detected event. Such at least one entity may also be an individual who has an expertise in the domain corresponding to the at least one portion of the technical installation 108 and is capable of resolving the detected anomaly in the technical installation 108. On identification of the escalation matrix, the escalation matrix is displayed on the display unit of the wearable device 107a-c of the entity, at step 902. The representative view 1101 and the predictive time series analysis of the portion of the technical installation 108 is shared with the at least one entity included in the escalation matrix, on the wearable device 107a-c associated with such entity, at step 903.

At step 1002 of the method 1000, an input is received from a first entity 1103a of the one or more entities through the user interface of the wearable device 107a-c of the first entity 1103a. The input from the first entity 1103a may be, for example, but not limited to, touch based or gesture based. Such input may be received via the user interface of the wearable device 107a-c. Alternatively, the input from the first entity 1103a may also be a voice based input which may be received through a voice user interface in order to initiate a service or process in the system 101. At step 1003, the input provided by the first entity 1103a is transmitted in real-time to the connected wearable devices 107a-c of the remain-

ing entities through the communication channel 1100. FIG 11 illustrates an embodiment of the representative view 1101 of the technical installation 108. In the embodiment, the holographic view 1101 of the technical installation 108 is viewed by the first entity 1103a and the second entity 1103b. In the embodiment, the gaze of the first entity 1103a is shared with the second entity 1103b and vice versa, so that both the entities 1103a, 1103b are aware of each other's point of view on the holographic view 1101. Therefore, if the first entity 1103a provides an input on the holographic view 1101 (or the portion of the holographic view 1102) of the technical installation 108, such input is transmitted to the wearable device second entity 1103b in real-time. Similarly, at step 1004, an input from the second entity 1103b may be received through the user interface of the wearable device, in response to the input from the first entity 1103a. In another embodiment, a conference session may be set up between the wearable devices 107a-c of the one or more entities 1103a, 1103b. The conference session facilitates efficient and quick sharing of information between different entities, thereby enabling effective management of the technical installation 108. The conference session, may be, for example a telephonic call between the entities associated with the connected wearable devices 107a-c. Therefore, the one or more entities may participate in the call either via voice and video or only via voice. In an embodiment, the conference session may be secured by a security code or a personal identification number (PIN) such that only authorized entities may participate in the session. The conference session enables participation of one or more entities present in different locations. Therefore, one or more entities may provide their inputs remotely.

FIG 12 illustrates an embodiment of a graphical user interface 1200 in conjunction with the representative view 1101 of a portion of the technical installation 108. The representative view 1101 of the technical installation 108 may be blown-up to provide a view of one or more units 1201, 1202 present inside the technical installation 108. The one or more entities may enable the blown-up view of the technical installation 108 to obtain a detailed understanding of the units present in the portion of the technical installation 108. In another embodiment, a zoomed view of the technical installation 108 may also be generated. For example, in an embodiment, the first entity 1103a through an input may visualize the zoomed view of the technical installation 108, wherein the unit 1201 may be displayed. The one or more entities 1103a, 1103b may further zoom in to the unit 1201 to visualize specific components 1202 within the unit 1201. The zoomed view provides information on linked connections between one or more components in the units. In an embodiment, the representative views 1101, 1201, 1202 of the technical installation 108, the unit and the components within the unit may include one or more tool-tips 1204a-e. A tool-tip is a graphical user interface element containing information related to an associated item. For

example, a tool-tip for the component 1202 may indicate the name of the component, the function of the component, one or more parameters associated with the component and an error message if the component is malfunctioning. In an embodiment, the tool-tip may not be shown unless a cursor is moved onto the item. Therefore, the tool-tip may be displayed only when a pointing device is hovered over the item. The tool-tip 1205a-b may also be present indicating information about one or more entities that are connected via the communication channel 1100. The graphical user interface 1200 may also include a manipulation toolbar 1203 which enables the one or more entities 1103a, 1103b to provide inputs on the representative views 1101, 1201, 1202 of the technical installation 108 and the units in the portion of the technical installation 108. In an embodiment, the manipulation toolbar 1203 may be active only for a single entity at a given point in time. Therefore, only a single entity may provide input at a given point in time. This prevents conflict between holograms.

The method 300 in FIG 3 further includes a step 305 of performing at least one mitigation action to address the detected event in the portion of the technical installation 108 based on the predictive time series analysis. FIG 6 illustrates an embodiment of a method 600 of performing a mitigation action to address the detected event. The method 600 includes a step 601 of detecting an anomaly associated with the event in the portion of the technical installation 108. The anomaly may be detected based on the predictive time series analysis of the received parameter values. The predictive time series analysis provides an understanding of which parameter may have deviated from the standard or threshold, thereby causing the anomaly. At step 602, a mitigation action is determined to resolve the detected anomaly. FIG 7 illustrates a flowchart of an embodiment of a method 700 of determining the mitigation action to resolve the detected anomaly. At step 701, an event log associated with the technical installation 108 may be obtained from the technical database 102. The event log may pertain to the occurrences in the portion of the technical installation 108. The event log may include recordings related to significant events occurring in the technical installation 108 such as to errors, warnings, and informational messages.

The event log may include a record of the time and date of occurrence of the event, type of event, source of the event and/or an event ID. At step 702, the event log is analyzed to determine of the nature and cause of the detected event. An event is reconstructed based on the event log to determine the cause of the malfunction or anomaly in the portion of the technical installation 108. The events in an event log may be stored chronologically and may be replayed in the same order to reconstruct the event, for example, in the form of a process history. The events may be reconstructed and represented on a map. For example, a map designer well known in the state of the art may be used to generate a map on

which the event may be reconstructed. The map may be, for example, but not limited to, Cartesian map, timeline based map or a process model map. Based on the reconstructed event, one or mitigation actions are identified at step 704 that may have been used to address similar events in the same technical installation 108 or different technical installations of similar nature. Alternatively, if the detected event is unique and may not have been addressed before, a mitigation action is determined by identifying steps that may be taken to overcome the anomaly and reduce the impact of the malfunction of the technical installation 108. In an embodiment, the one or more identified mitigation actions may be shared with the one or more entities associated with the one or more wearable devices 107a-c, through the communication channel 1100. At 705, at least one mitigation action is determined from the identified mitigation actions to resolve the detected event.

FIG 8 illustrates a flowchart of an embodiment of a method of determining the most appropriate mitigation action to resolve the detected anomaly. At step 801, a predictive time series analysis data for each of the identified mitigated actions is obtained. In an embodiment, the predictive time series analysis data for each of the mitigation actions may be generated in a way similar to the predictive time series analysis for the detected event. The predictive time series analysis data for the mitigation actions enables the maintenance management system 101 to determine how the functioning of the technical installation 108 may change with time. Predictive time series analysis data may be generated by identifying one or more parameters that may be affected by the implementation of the mitigation action. Once the parameters are identified, a pre-defined threshold value for each of the parameters may be identified. In an embodiment, a prediction model may be used to determine probable estimate values of the parameters. The probable estimate values may be determined based on one or more factors associated with each of the mitigation actions. For example, if a successful implementation of a mitigation action depends on the effective functioning of another conjugated unit in the technical installation 108, the working status of such conjugated unit is determined. The probable estimate values may be distributed over a period of time to generate a predictive time series analysis data for each of the mitigation actions. At step 802, the outcome of each of the mitigation actions is determined by analyzing the predictive time series analysis data. For example, if the conjugated unit of the technical installation is non-functional, the outcome of the implementation of the mitigation action would be negative. Implementation of such mitigation action may lead to a catastrophic disaster in the technical installation 108, or permanently damage the portion of the technical installation 108. Therefore, determining the outcome of each mitigation action enables the one or more entities 1103a, 1103b to take an informed decision for efficient maintenance of the technical installation 108. At step 803, a mitigation

action with the most appropriate outcome in comparison to the other outcomes of the identified mitigation actions is determined to resolve the detected anomaly. On determination of the most appropriate mitigation action, at step 603 of method 600, the mitigation action may be performed in the portion of the technical installation 108 to resolve the detected anomaly.

10

15

Patent claims

1. A method (300) of managing a technical installation (108), the method (300) comprising:
5 detecting an event associated with at least a portion of the technical installation (108) based on sensor data associated with the portion of the technical installation (108);
rendering a representative view (1101) of the portion of the technical installation (108) on
at least one wearable device (107a-c), wherein the representative view displays infor-
10 mation associated with the detected event in conjunction with a multi-dimensional view of
the portion of the technical installation (108);
generating predictive time series analysis of the sensor data associated with the detected
event; and
displaying the predictive time series analysis in conjunction with the representative view
15 (1101) of the at least one portion of the technical installation (108).
2. The method (300) according to claim 1, wherein detecting the event in the portion
of the technical installation (108) comprises:
receiving the sensor data associated with the at least one portion of the technical installa-
20 tion (108) from one or more sensor units disposed in the technical installation (108);
analyzing the sensor data associated with the at least one portion of the technical installa-
tion (108); and
detecting the event associated with the portion of the technical installation (108) based on
the analyzed sensor data.
25
3. The method (300) according to claims 1 or 2, wherein generating the predictive
time series analysis of the sensor data comprises:
identifying one or more parameters associated with the functioning of at least the portion
of the technical installation (108);
30 identifying a threshold value for each of the one or more parameters;
receiving real-time values of the one or more parameters associated with the functioning
of at least the portion of the technical installation (108) from the one or more sensor units,
wherein the values comprise a time stamp; and
generating the predictive time-series analysis associated with the event using the received
35 real-time values.

4. The method (300) according to claim 3, wherein generating the predictive time series analysis comprises:

determining one or more probable estimate values of the one or more parameters based on the real-time values received from the one or more sensors; and

5 distributing the one or more probable estimate values of the one or more parameters at regular intervals of time to generate the predictive time series analysis.

5. The method (300) according to any of the claims 1 to 4, further comprising:

10 detecting an anomaly associated with the event in the portion of the technical installation (108) based on the predictive time series analysis of the received values;

determining a mitigation action to resolve the detected anomaly; and

performing the mitigation action to resolve the anomaly in at least the portion of the technical installation (108).

15 6. The method (300) according to claim 5, wherein in determining the mitigation action to resolve the detected anomaly comprises:

obtaining an event log associated with the technical installation (108) from a technical database (102);

20 analyzing the event log corresponding to the at least one portion of the technical installation (108);

reconstructing an event based on the event log to determine the cause of the malfunction in the portion of the technical installation (108);

identifying one or more mitigation actions previously used for addressing a similar event in the same or a different technical installation (108); and

25 determining a mitigation action for resolving the detected anomaly associated with the portion of the technical installation (108) from the identified mitigation actions.

7. The method (300) according to claim 6, wherein determining the mitigation action for resolving the detected anomaly comprises:

30 obtaining a predictive time series analysis data for each of the identified mitigation actions;

determining an outcome of each mitigation action by analyzing the predictive time series analysis data for each of the identified mitigation actions; and

determining a mitigation action with the most appropriate outcome in comparison to the other outcomes of the identified mitigation actions to resolve the anomaly.

35

8. The method (300) according to any of the claims 1 to 7, further comprising establishing a communication channel (1100) between the at least one wearable device (107a)

and other wearable devices (107b-c) of one or more entities associated with the technical installation (108).

9. The method (300) according to claim 8, further comprising:

- 5 identifying an appropriate escalation matrix associated with the detected anomaly, where-
in the escalation matrix comprises at least one entity to be reported regarding the detect-
ed anomaly;
displaying the mitigation action and the corresponding escalation matrix on the wearable
device (107a-c); and
10 sharing the mitigation action and the corresponding escalation matrix by the at least one
entity to at least one wearable device (107a-c) of the at least one entity in the escalation
matrix over the established communication channel (1100).

10. The method (300) according to claim 8 or 9, further comprising setting up a con-
15 ference session between the connected wearable devices (107a-c) via the communication
channel (1100).

11. The method (300) according to any of the claims 6 to 8, further comprising:
sharing the representative view (1101) and the predictive time series analysis of the por-
20 tion of the technical installation (108) with the connected wearable devices (107a-c) of one
or more entities via the communication channel (1100);
receiving an input from a first entity of the one or more entities through a user interface of
the wearable device (107a) of the first entity;
transmitting the input provided by the first entity in real-time to the connected wearable
25 devices (107b-c) of the remaining entities through the communication channel (1100); and
receiving an input from a second entity of the one or more entities through the user inter-
face of the wearable device (107b-c) of the second entity in response to the input of the
first entity.

- 30 12. The method (300) according to claim 1, further comprising generating an alert on
the at least one wearable device (107a-c) when the event associated with the portion of
the technical installation (108) is detected.

- 35 13. A system (101) comprising:
one or more servers remotely located from a technical installation (108);
one or more sensors communicatively coupled to the one or more servers; and

one or more wearable devices (107a-c) communicatively coupled to the one or more servers, wherein the one or more servers comprise computer readable instructions, which when executed by the one or more servers cause the one or more servers to perform the method (300) according to claims 1 to 12.

FIG 1




FIG 2




FIG 3




FIG 4




FIG 5




FIG 6




FIG 7




FIG 8




FIG 9




FIG 10




FIG 11




FIG 12





FIG 13



INTERNATIONAL SEARCH REPORT

International application No

PCT/ EP20 19/0590 11

A. CLASSIFICATION OF SUBJECT MATTER
 I NV . G05B23/02
 ADD .
 According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED
 Minimum documentation searched (classification system followed by classification symbols)
 G05B
 Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched
 Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)
 EPO- Interna l , WPI Data

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 2 884 363 A2 (HITACHI HIGH TECH CORP [JP]; HITACHI POWER SOLUTIONS CO LTD [JP]) 17 June 2015 (2015-06-17) the whole document -----	1,13
A	GB 2 513 238 A (FISHER ROSEMOUNT SYSTEMS INC [US]) 22 October 2014 (2014-10-22) the whole document -----	1,13
A	US 2015/316907 A1 (ELBSAT MOHAMMAD N [US] ET AL) 5 November 2015 (2015-11-05) the whole document -----	1,13
A	US 2013/173218 A1 (MAEDA SHUNJI [JP] ET AL) 4 July 2013 (2013-07-04) figure 20A -----	1,13

Further documents are listed in the continuation of Box C.

See patent family annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier application or patent but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search 29 May 2019	Date of mailing of the international search report 12/06/2019
Name and mailing address of the ISA/ European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Fax: (+31-70) 340-3016	Authorized officer Kuntz, Jean-Marc

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No PCT/EP2019/059011

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 2884363	A2	17-06-2015	EP 2884363 A2 17-06-2015
			JP 6216242 B2 18-10-2017
			JP 2015114967 A 22-06-2015
			US 2015169393 A1 18-06-2015

GB 2513238	A	22-10-2014	CN 104049586 A 17-09-2014
			DE 102014103486 A1 18-09-2014
			GB 2513238 A 22-10-2014

US 2015316907	A1	05-11-2015	EP 3062183 A1 31-08-2016
			EP 3062184 A1 31-08-2016
			US 2015316901 A1 05-11-2015
			US 2015316902 A1 05-11-2015
			US 2015316903 A1 05-11-2015
			US 2015316907 A1 05-11-2015
			US 2015316946 A1 05-11-2015
			US 2019107825 A1 11-04-2019

US 2013173218	A1	04-07-2013	JP 5501903 B2 28-05-2014
			JP 2012058890 A 22-03-2012
			US 2013173218 A1 04-07-2013
			WO 2012032812 A1 15-03-2012
