

## **New Life for Old Buildings**

### **A new evaluation instrument for matching the market supply of vacant office buildings and the market demand for new homes**

Geraedts, RP; van der Voordt, DJM

#### **Publication date**

2008

#### **Document Version**

Final published version

#### **Published in**

The Architecture Annual 2006 - 2007

#### **Citation (APA)**

Geraedts, RP., & van der Voordt, DJM. (2008). New Life for Old Buildings: A new evaluation instrument for matching the market supply of vacant office buildings and the market demand for new homes. In H. Bekkering, A. ten Doeschate, D. Hauptmann, A. den Heijer, U. Knaack, & S. van Manen (Eds.), *The Architecture Annual 2006 - 2007* (pp. 88-93). 010.

#### **Important note**

To cite this publication, please use the final published version (if applicable).  
Please check the document version above.

#### **Copyright**

Other than for strictly personal use, it is not permitted to download, forward or distribute the text or part of it, without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license such as Creative Commons.

#### **Takedown policy**

Please contact us and provide details if you believe this document breaches copyrights.  
We will remove access to the work immediately and investigate your claim.

# New Life for Old Buildings

## A new evaluation instrument for matching the market supply of vacant office buildings and the market demand for new homes

ROB GERAEDTS AND THEO VAN DER VOORDT

### *Introduction*

In the Netherlands, both the office market and housing market show a mismatch between supply and demand, quantitatively and qualitatively. In 2007 almost 14% of all offices are vacant, i.e. 5.9 million square metres. Experts judge at least 1 million m<sup>2</sup> as having no chance at all to be let again as an office. At the same time we see a shortage of about 1 million dwellings.

The future is uncertain – the present must be adaptable. A building must be able to be changed over its life cycle to adapt to the inevitable evolving needs of its end users. Buildings must remain efficient places to live and work to ensure real life-cycle value, driven by the 3 R's of reduce-reuse-recycle. The first real challenge in the Netherlands is how to make adaptable buildings without creating unnecessary redundancy and without significantly increasing the initial cost. The second challenge is the re-use of old vacant or unoccupied buildings – left by their tenants because they no longer fulfilled their needs – because the available area for erecting new ones is very scarce in the Netherlands. In this matter, old buildings deserve a second chance in their life cycle.

Therefore it is important to have effective means of determining the transformation potential of buildings that are unoccupied or are likely to become unoccupied in the near future. We need to be able to measure this transformation potential at both location and building level, and it will be convenient to be able to carry out both a quick, superficial appraisal (which we may call a 'Quick Scan') and a more thorough, detailed study (a 'feasibility scan'). To this end, we have developed what we call a 'Transformation Potential Meter' for office buildings (Geraedts and Van der Voordt, 2002, 2004). This instrument is basically a number of checklists containing both veto criteria and gradual criteria that can be used to determine which features of the location and the building favour successful transformation into housing, and which hinder it.

The meter has been tested in practice by a number of market players, and has also been widely used by students of architecture who are nearing the end of their degree course. As befits good students, they have subjected the instrument to critical appraisal. Details of the use to which they have put the meter, and their appraisal of it, may be found e.g. in the master's theses prepared by Nicole de Vrij, Klaas Jan Boer, John Magielsen, Kawai Pang and Niels Jongeling.

This practical application has allowed the transformation potential meter to be evaluated and refined in 2006. Two new steps – the financial feasibility scan and the risk assessment checklist – have also been added to permit further investigation of the feasibility of a transformation project. In this paper, we describe the principle of the new transformation potential meter and its position in the go/no-go decision-making process in the

initial phase of a transformation project. This contribution is based in part on a literature survey on how the features of locations and buildings determine the choice of housing. Interviews were also held with parties involved in the transformation process in the Netherlands. The interviewees were asked, among other things, which features of locations and buildings they considered to be most relevant to the transformation process (fig. 1).

### *Vacant office buildings*

According to experts from the world of professional practice, the transformation prospects of the current offering of office buildings depend primarily on the following three factors:

#### *1. Duration of vacancy*

The longer an office building is unoccupied, the readier the current owner will be to convert it so that it can be used for another purpose.

#### *2. Reason for vacancy: market, location or building*

When an office building is unoccupied because of market factors, transformation would not seem to be an attractive option from the owner's viewpoint if the market is strengthening. If the location is unsuitable for office purposes and/or the building does not meet (or no longer meets) the requirements for office use, transformation may be a good idea. If the vacancy is due to building-related factors, the transformation potential is highly dependent on the extent to which the building can be converted by design interventions into an attractive residential property meeting the requirements and wishes of local target groups. Financial feasibility and permission to modify the zoning plan are critical factors for success in this context.

#### *3. Municipal policy*

When the office building in question lies in an area that has been prioritised for residential use by the municipal authorities, transformation into residential housing would seem to be an obvious solution since this is in line with municipal policy. If on the other hand the building is in an area earmarked for development or redevelopment for office use, renovation and reuse for office purposes would seem to be more appropriate.

### *Market demand for new homes*

Transformation of unoccupied offices into homes only makes sense if the dwelling units produced meet a need. The supply must be in line with the demand, as regards both the location – which should be a residential environment – and the features of the building (an office building will in general be converted into a block of flats comprising individual dwelling units). Since nearly a quarter of people looking for housing in the Netherlands are under 25 (including many students), transformation into low-cost accommodation may be a good choice. Where high-rise office buildings are concerned, transformation into accommodation for families with young children is less appropriate. Conversion into flats for senior citizens might be a good choice here for the Dutch situation (see Table 1)

If one wishes to use a Quick Scan to determine whether an unoccupied (office) building is suitable for transformation into residential accommodation for one or more specific target groups, a demand profile must first be created for each target group. This is also necessary when looking for a suitable building for a specific target group. The five Dutch target-group profiles shown in Table 1 have been defined on the basis of the dwelling preferences of the people concerned.

Table 1: Five Dutch Target-group Profiles with dwelling preferences for inner-city transformations

**Target group 1: Starters**  
Young, low-income singles  
Shared accommodation

*Location (dwelling environment)*

1. Urban environment
2. Plenty of amenities

*Building (features of dwelling)*

3. Unit in group of 3-7 occupants
4. Bedsit, coverage 22m<sup>2</sup>
5. Shared sanitary facilities  
1 shower/toilet per 4 units
6. Shared kitchen with table farmhouse
7. Shared outside space (garden, etc.)  
1.5 m<sup>2</sup>/unit
8. Shared cycle storage
9. Shared washroom
10. Total 50m<sup>2</sup>, useful floor area 35 m<sup>2</sup>

*Cost*

11. Max. rent 160 - 220 Euro

**Target group 3: Young, two-income**  
Low to middle income

*Location (dwelling environment)*

1. Safe dwelling environment (social safety)
2. Shops, daily amenities and public transport within walking distance (~500 m)
3. Urban environment
4. Suburban front space, green

*Building (features of dwelling)*

5. Preferably not on ground floor
6. With lift in building
8. Preferably not with internal staircase
9. At least 3 rooms
10. Living room 25 - 30m<sup>2</sup>, bedroom > 11.5m<sup>2</sup>
11. Direct link living room, bedroom, bathroom
12. Extra attention to acoustic insulation
13. Adaptable for disabled occupants

**Target group 2: Starters**  
Young, low-income singles  
Semi-independent accommodation

*Location (dwelling environment)*

1. Urban environment
2. Plenty of amenities

*Building (features of dwelling)*

3. Semi-independent unit with shared facilities
4. Bedsit, coverage 20 m<sup>2</sup>
5. Sanitary facilities for 2 persons
6. Kitchen for 2 persons
7. Shared outside space (garden, etc.)  
1.5m<sup>2</sup>/unit
8. Shared cycle storage
9. Shared washroom
10. Total 50m<sup>2</sup>, useful floor area 35m<sup>2</sup>

*Cost*

11. Max. rent €20 - 300 Euro

**Target group 5: Senior citizens 55+**  
Above-middle income

*Location (dwelling environment)*

1. Safe dwelling environment (social safety)
2. Shops, daily amenities and public transport within walking distance (~500 m)
3. Easily accessible by car
4. Good parking facilities
5. Some like urban, some like suburban

*Building (features of dwelling)*

6. Preferably not on ground floor
7. With lift in building
8. Preferably not with internal staircase
9. Access via entrance hall, not via gallery
10. 4 - 5 rooms
11. Living room 30 - 40m<sup>2</sup>, big kitchen
12. Direct link living room, bedroom, bathroom
13. Amply sized bathroom
14. Balcony or roof garden 10 - 15m<sup>2</sup>
15. Extra attention to acoustic insulation
16. Adaptable for disabled occupants

*Cost*

17. Rent 550 - 1100 Euro
18. Rent > 1100 Euro for top flat
19. Purchase 110,000 - 300,000 Euro

**Target group 4: Young, two-income**  
Young couples with two incomes

*Location (dwelling environment)*

1. Urban environment
2. Plenty of amenities
3. Suburban front space, green
4. Easily accessible by car
5. Good parking facilities

*Building (features of dwelling)*

6. Big luxury flat
7. Own outside space (garden, etc.)

*Cost*

8. Max. rent 550 - 750 Euro
9. ditto 750 - 1000 Euro for top flat
10. Purchase 100,000 - 200,000 Euro

Table 2: The various steps of the New Transformation Potential Meter

Step	Action	Level	Outcome
Step 0	Inventory market supply of unoccupied offices	Stock	Location of unoccupied offices
Step 1	Quick Scan: initial appraisal of unoccupied offices using veto criteria	Location Building	Selection or rejection of offices for further study, GO / NO GO decision
Step 2	Feasibility scan: further appraisal using gradual criteria	Location Building	Judgement about transformation potential of office building
Step 3	Determination of transformation class	Location Building	Indicates transformation potential on 3-point scale from very good to NO GO
<b>Further analysis (optional, and may be performed in reverse order if as desired):</b>			
Step 4	Financial feasibility scan using design	Building	Indicates financial/economic feasibility Sketch and cost-benefit analysis
Step 5	Risk assessment checklist	Location Building	Highlights areas of concern in transformation plan

Table 3: Step 1 – The Quick Scan with the aid of Veto Criteria

step 1 Quick Scan: Initial Assessment Using Veto Criteria		
Aspect	Veto Criteria	Data Source
<b>Market</b>		
1 Demand for housing	1 There is no demand for housing from local target groups	Estate agent/municipality
<b>Location</b>		
2 Urban location	2 Zoning plan does not permit modification 3 Serious public health risk (pollution, noise, odour)	Zoning plan/municip. policy Estate agent/on-site inspect.
<b>Building</b>		
3 Dimensions of skeleton	4 Free ceiling height < 2.60m	Estate agent/on-site inspect.
<b>Organisation</b>		
4 Banker for transformation plan	5 There is no enthusiastic, influential banker	Local investigation
5 Internal veto criteria of property developer	6 Does not meet criteria for region/location/accessibility	Property developer
6 Owner/investor	7 Does not meet criteria on size and character of building 8 Not willing to sell office building	Property developer Owner

### The new transformation potential meter

The information collected about transformation prospects, housing requirements of potential occupants and target-group profiles has been used as a basis for a number of checklists that can be used to appraise the potential of the stock of unoccupied office buildings for transformation into residential housing. This appraisal takes place in a number of steps, from more superficial to more detailed and specific (see Table 2).

#### Step 0: Inventory of supply at district level

Before starting to use the transformation potential meter proper, an inventory should first be taken of the market supply of office buildings in a given municipality that have been unoccupied in the long term or may be expected to become unoccupied in the near future. Information for this purpose may be obtained from literature surveys, data from estate agents or the investigator's own observations. If adequate information is already available about a given unoccupied building, this step can be skipped.

#### Step 1: Quick Scan; first impression, evaluation with aid of veto criteria

The instrument offers the user the possibility of performing a quick initial appraisal of the transformation potential, which is not very labour-intensive and does not require much data. This quick scan makes use of eight veto criteria that fall under the headings Market, Location, Building and Organisation (see Table 3).

A veto criterion is a criterion which if satisfied (if the answer to the relevant question is 'Yes') leads to immediate rejection of the idea of transforming the office premises in question into residential accommodation. Further detailed study is then no longer necessary. This is therefore an effective means of picking out promising candidates for transformation quickly from the overall potential market.

The veto criteria apply to all target groups. Veto criteria 2 and 3 at location level concern the situation of the building within the urban fabric. If for example the office building is located on an industrial site where serious public-health hazards have been discovered, or if the municipal authorities do not allow any modification of the zoning plan at this location, there is little point in taking the investigation of the transformation potential any further.

#### Step 2: Feasibility scan based on gradual criteria

If the results of the Quick Scan indicate that there is no immediate objection to transformation (no single question is answered 'Yes'), the feasibility of transformation can be studied in greater detail with reference to a number of 'gradual' criteria, i.e. criteria that do not lead to a go/no-go decision but that express the transformation potential of the building in question in terms of a numerical score. Taken together, these criteria allow a more rounded picture to be built up of the feasibility of the transformation project (see Table 4).

The feasibility scan at location level (Table 4) comprises 7 main criteria, subdivided into functional, cultural and legal aspects, and 23 sub-criteria. The feasibility scan at building level (Table 5) comprises 13 main criteria, subdivided into functional, technical, cultural and legal aspects, and 13 sub-criteria.

An answer 'Yes' to any question indicates somewhat lower suitability for transformation – though not severe enough for out-and-out rejection. At the end of the scan, the Yeses are added up to obtain the overall transformation potential score – the lower the better. This is described under step 3 below (see Table 5).

### Step 3: Determination of the transformation class

The results of the feasibility scan can be used to calculate a transformation-potential score for the building in question, on whose basis the building can be assigned to one of five transformation classes ranging from 'ideal for transformation' to 'not suitable for transformation' (Table 6).

Table 6: The total transformation-potential scores at Location and Building level are determined by multiplying the number of Yeses in the Appraisal column by the default weighting factor

Total number of Yes (Location)	8	x
Default weighting	5	=
Score (Location)	40	A
Max possible score (23x5)	115	
Total number of Yes (Building)	11	x
Default weighting	3	=
Score (Building)	33	B
Max possible score (13x3)	39	

The total scores for the location and the building are determined by multiplying the number of Yeses in the respective tables by a weighting factor, which has provisionally been chosen as 5 for the location and 3 for the building to reflect the greater relative importance of the location in these considerations.

On the basis of the transformation-potential score, the building can be assigned to one of five Transformation classes. Buildings in Transformation Class 1 (score lower than 40), are highly suitable for transformation into residential accommodation, while those in Class 5 (score higher than 161) are totally unsuitable for transformation. All five Transformation classes are given in Table 7.

Table 7: Transformation classes for office buildings; in the example shown, a total score of 77 corresponds to Transformation class 2 (transformable)

Step 3: Determination of Transformation Class of Office Building		
Transformation score Location + Building	= 0 - 40	Transformation class 1: Excellent transformability
	= 41 - 80	Transformation class 2: Transformable
	= 81 - 120	Transformation class 3: Limited transformability
	= 121 - 160	Transformation class 4: Very poor transformability
	= 161 - 199	Transformation class 5: Not Transformable
<p>← Total Score A + B: 73</p> <p>Max Score Location + Building = 115 + 39 = 154</p> <p>→ Transformation class: 2</p>		

Determination of the transformation class of a building completes the first three steps of the transformation potential measurement. If the results indicate that the building lends itself to transformation (i.e. that it falls into transformation class 1 or 2), the analysis can continue in two additional steps, aimed at studying the financial feasibility of the transformation project and carrying out a risk assessment for use in further planning.

Table 4: Step 2a – Appraisal of suitability of an office building for transformation into homes at location level

Step 2: Feasibility Scan Using Gradual Criteria			
Aspect	Gradual Criterion	Data Source	Appr. Yes
<b>Functional</b>			
1 Urban location	1 Building in industrial estate or office park far from town centre 2 Building gets little or no sun 3 View limited by other buildings on > 75% of floor area	Town map On-site inspection On-site inspection	
2 Distance and quality of amenities NB The quality of amenities can be described in terms of number, variety and level of services provided	4 Shops for daily necessities > 1 km. 5 Neighbourhood meeting place (square, park) > 500 m 6 Hotel/restaurant/cafe/bar > 500 m 7 Bank/Post Office > 1 km. 8 Basic medical facilities (practice, health centre) > 5 km. 9 Sports facilities (lenses, swimming pool, sports park) > 2 km. 10 Education (from kindergarten to university) > 2 km.	On-the-spot investigation ditto ditto ditto ditto ditto	
3 Public transport	11 Distance to railway station > 2 km. 12 Distance to bus/underground/train > 1 km.	Town map Map or transport services	
4 Accessibility by car and parking (obstacles: narrowing of road, speed bumps, bridges) Congestion: 1-way traffic, no parking, tail-back	13 Many obstacles, traffic congestion 14 Distance to parking sites > 250 m. 15 <1 parking space/100m <sup>2</sup> road surface	On-the-spot investigation Inspection/new design Inspection/new design	
<b>Cultural</b>			
5 Tone of neighbourhood NB Assessment depends on target group, e.g. young people not in mono-functional neighbourhood 55+ not on edge of town	16 Situated on or near edge of town (e.g. near motorway) 17 No other buildings in immediate vicinity 18 Drab environment 19 No green space in neighbourhood 20 Area has poor reputation/image, vandalism 21 Dangerous, noise or odour pollution (factories, trains, cars)	Map or estate agent Map or estate agent On-the-spot investigation On-the-spot investigation Inspection and local press On-the-spot investigation	
<b>Legal</b>			
6 Urban location	22 Noise load on facade > 50 dB (limit for office B0dB)	Municipal authorities	
7 Ownership of ground	23 Leasehold	Estate agent	

Table 5: Step 2b - Appraisal of suitability of an office building for transformation into homes at building level

Building			
Aspect	Gradual Criterion	Data Source	Appr. Yes
<b>Functional</b>			
1 Year of Construction or renovation	1 Office building recently built (< 8 years) 2 Recently renovated as office (< 8 years)	Year of construction Year of construction	
2 Viability	3 Some office space still in use 4 Building unoccupied < 3 years	e.g. NEPRON ditto	
3 Features of new dwelling units	5 ≤ 20-person units (30m <sup>2</sup> estd) can be made 6 Layouts suitable for local target groups can't be implemented	≤ 1000m <sup>2</sup> useful area Design sketch	
4 Extensibility	7 Not horizontally extendable (neighbouring buildings) 8 No extra storeys (pitched roof, no sufficient load-bearing cap.) 9 Basement cannot be built under building	On-the-spot investigation On-the-spot investigation Inspection and/or estate agent	
<b>Technical</b>			
5 Maintenance	10 Building poorly maintained/looks in poor condition	External visual inspection	
6 Dimensions of facade Module of facade determines pitch of roof	11 Office depth < 10m 12 Module of support structure < 5.60m 13 Distance between floors > 5.00m	Estate agent or inspection On-site or estate agent On-site or estate agent	
7 Support structure (walls, pillars, floors)	14 Support structure in poor/hazardous condition	On-site inspection	
8 Façade Entrance space dependent on target group Proportions of windows, doors or adaptations	15 Can't be made to blend with surrounding environment > 5.40m 16 Façade (or openings in façade) not adaptable 17 Windows cannot be reused/opened	On-site or estate agent On-site inspection Inspection/new design	
9 Installations	18 Impossible to install sufficient service ducts	Inspection/new design	
<b>Cultural</b>			
10 Character of location, "tone of neighbourhood"	19 No character in relation to surrounding buildings 20 Impossible to create dwellings with an identity of their own 21 Unsafe entrance, no clear overview of situation	On-site inspection Inspection/new design Inspection/new design	
<b>Legal</b>			
12 Environment Exposure to sunlight, air and noise pollution, hazardous materials	22 Presence of large amounts of hazardous materials 23 Acoustic insulation of floors < 4 dB 24 Very poor thermal insulation of outer walls and/or roof 25 < 10% of floor area of new units gets incident daylight	On-site or municipality Inspection/new design On-site or municipality On-site inspection	
13 Requirements of Besluit (Dutch office regulations and standards for the building industry)	26 No lifts in building (> 4 storeys), no lifts can be installed 27 No (emergency) staircase	On-site or estate agent Inspection/new design	

## References

Voordt, D.J.M. van der et al. (2007), *Transformatie van Kantoorgebouwen*, 010 Publishers, Rotterdam.

Jongeling, N. (2006), *Transformatiepotentie van RABO Bank kantoren*. Master's thesis, Faculty of Architecture, Delft University of Technology.

Pang, K. (2006), *Nieuwe woningen in een oud kantoor*. Master's thesis, Faculty of Architecture, Delft University of Technology.

Geraedts, R.P. (2005), *Offices for Living in*. Paper, International Workshop on Activation and Renewal of Building Stocks, 4-Met Center, Tokyo Metropolitan University.

Boer, K.J. (2004), *Tijdelijke transformatie van kantoren naar woningen*. Master's thesis, Faculty of Architecture, Delft University of Technology.

Magielsen, J. (2004), *Transformatie, interessant voor beleggers?* Master's thesis, Faculty of Architecture, Delft University of Technology.

Vrij, N. de (2004), *Transformatiepotentie: meten is weten*. Master's thesis, Faculty of Architecture, Delft University of Technology.

Geraedts, R.P. and D.J.M. van der Voordt (2004), *Transformation of Office Buildings: An instrument for measuring the potential for transforming offices into homes*, CIB World Congress, Toronto.

Geraedts, R.P. and D.J.M. van der Voordt (2002), *Transformation of Office Buildings*. Abstract & paper, Proceedings CIB W104 Open Building Implementation, Mexico.

### *Step 4: Financial feasibility scan*

If the transformation project is not financially feasible, there is no point in taking the plans any further. The financial feasibility depends among other things on the acquisition costs, the current condition of the building, the amount of renovation or modification work required, the number of dwelling units that could be created in the building and the project yield in the form of rental income and/or sales prices.

In order to determine the financial feasibility, answers must be obtained to a number of questions concerning both the project costs and the expected revenue. On the benefit side, we need to know how many dwelling units can be created and for what target groups they are intended. These questions can only be answered if a sketch has been made of the intended layout of the building after transformation. The financial feasibility can be raised by increasing the size of the building, e.g. by adding extra storeys on top, or by the inclusion of commercial functions alongside the residential ones.

On the costs side, it is necessary to know the acquisition costs for the premises, including the cost of the ground. Building and installation costs are also an important factor. What is the current condition of the building? Which parts can be reused, and which will have to be demolished? What is the ratio of facade surface area to gross floor area (GFA)? To what level should the building be finished? To what extent can the existing stairways, lifts and other means of access, and facade proportions be maintained?

Table 8 gives some key figures that can be used for a quick cost-benefit analysis based on initial design sketches. It shows the estimated range of total investment costs (acquisition and building costs) for the transformation of existing (office) buildings to student accommodation, per dwelling unit and per m<sup>2</sup> of GFA, compared with the costs of comparable new buildings. After a rough cost-benefit analysis has been made on the basis of a sketch of the way in which various dwelling types and layouts can be fitted into the existing office building, this data can be used as input for the development plans of the property developer.

### *Step 5: Risk assessment checklist*

When the Quick Scan indicates that the office building in question has transformation potential at both location and building level and the results of the initial financial feasibility analysis are also encouraging, work may proceed on the subsequent development phases. It is of great importance to be aware of the possible bottlenecks and risks that can occur during this process. Two checklists that can prove useful in this context have been developed, based on experience gained in a large number of projects.

### *Conclusions*

Practical trials of the Transformation Potential Meter in practice have revealed its utility for mapping the potential of given office buildings for transformation into residential accommodation in a number of steps from general to more detailed. It was found, however, that a number of veto criteria included in the original version of the meter were too stringent. Some buildings that failed to pass these criteria on paper were found in practice to lend themselves well to transformation into residential accommodation. For example, a project size of less than 20 dwelling units (2000 m<sup>2</sup>), a building that was still partially

occupied, a duration of vacancy of less than three years or an age of less than three years for the building in question, were not necessarily reasons for rejecting the idea of transformation. It was moreover found to be highly desirable to combine the first three stages of the Transformation Potential Meter (Quick Scan, feasibility scan and determination of transformation class) with a financial feasibility scan and a risk assessment (the readiness of the municipal authorities to approve any changes in the zoning plan required for success of the project is one of the points that needs to be thoroughly explored in advance in this context).



1a

Table 8: Expected investment costs per dwelling unit and per m2 GFA for student accommodation created by transformation of office buildings (ref. Stadswonen Rotterdam, index April 2006)

Type of construction project		Type of budget	Cost per unit	Costs per m <sup>2</sup> GFA
Transformation	Much demolition and modification	Acquisition budget for student unit	10,000 - 15,000	
		Residual budget for renovation costs	27,000 - 39,000	540 - 660
	Much reuse (including facade)	Acquisition budget for student unit	20,000 - 25,000	
		Residual budget for renovation costs	21,000 - 26,000	420 - 540
New construction	Student unit		96,000 - 99,000	720 - 780
	Social housing			890 - 970
	Luxury flat			1,100



1b



1c

1a  
Rotterdam. Puntegale  
Conversion (1999) of a former tax  
building (built in 1940-1945) into  
210 residential apartments for students  
and starting households, 2.500 m<sup>2</sup>  
of working accommodation, and  
a parking garage

1b  
Main hall

1c  
Dwelling