Pan-cancer subtyping in a 2D-map shows substructures that are driven by specific combinations of molecular characteristics

Taskesen, Erdogan; Huisman, Sjoerd; Mahfouz, Ahmed; Krijthe, Jesse; de Ridder, Jeroen; van de Stolpe, A.; van den Akker, Erik; Verhaegh, Wim; Reinders, Marcel

DOI
10.1038/srep24949
10.1038/s41598-018-35518-w

Publication date
2016

Document Version
Final published version

Published in
Scientific Reports

SCIENTIFIC REPORTS

OPEN

Published online: 23 November 2018

Author Correction: Pan-cancer subtyping in a 2D-map shows substructures that are driven by specific combinations of molecular characteristics

Erdogan Taskesen[1], Sjoerd M. H. Huisman[1,2], Ahmed Mahfouz[1,2], Jesse H. Krijthe[1], Jeroen de Ridder[1], Anja van de Stolpe[3], Erik van den Akker[1], Wim Verhaegh[3] & Marcel J. T. Reinders[1]

Correction to: *Scientific Reports* https://doi.org/10.1038/srep24949, published online 25 April 2016

This Article contains a typographical error in the spelling of the author Wim Verhaegh, which is incorrectly given as Wim Verheagh.

[1]Delft Bioinformatics Lab (DBL), Delft University of Technology, Delft, 2628CD, The Netherlands. [2]Division of Image Processing, Department of Radiology, Leiden University Medical Center, Leiden, The Netherlands. [3]Precision and decentralized Diagnostics, Philips Research, Eindhoven, The Netherlands. Correspondence and requests for materials should be addressed to M.J.T.R. (email: M.J.T.Reinders@tudelft.nl)