

Improved surface-wave response from ambient noise in Malargüe, Argentina, using seismic interferometry by multidimensional deconvolution

Weemstra, Kees; Draganov, Deyan; Ruigrok, Elmer

Publication date

2015

Document Version

Final published version

Citation (APA)

Weemstra, K., Draganov, D., & Ruigrok, E. (2015). *Improved surface-wave response from ambient noise in Malargüe, Argentina, using seismic interferometry by multidimensional deconvolution*. Abstract from Passive imaging and monitoring in wave physics, Cargese, Corsica, France.

Important note

To cite this publication, please use the final published version (if applicable). Please check the document version above.

Copyright

Other than for strictly personal use, it is not permitted to download, forward or distribute the text or part of it, without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license such as Creative Commons.

Takedown policy

Please contact us and provide details if you believe this document breaches copyrights. We will remove access to the work immediately and investigate your claim.

Improved surface-wave response from ambient noise in Malargüe, Argentina, using seismic interferometry by multidimensional deconvolution

Cornelis Weemstra¹, Deyan Draganov¹ & Elmer Ruigrok²

¹Department of Geoscience and Engineering, Delft University of Technology, 2600 GA Delft, The Netherlands

²Department of Earth Sciences, Utrecht University, Budapestlaan 4, 3584 CD Utrecht, The Netherlands.

Generating new seismic responses from existing recordings is generally referred to as seismic interferometry. Conventially, the new responses are retrieved by simple crosscorrelation of recordings made by separate receivers. The newly retrieved responses can be used to extract receiver-receiver phase velocities, which often serve as input parameter for tomographic inverse problems, or which can be linked to temporally varying parameters such as hydrocarbon production and precipitation. For all applications, however, the accuracy of the retrieved responses is of great importance. In practice, this accuracy is often degraded by irregularities in the illumination pattern: correct response retrieval relies on a uniform illumination of the receivers. Reformulating the theory underlying seismic interferometry by crosscorrelation as a multidimensional deconvolution (MDD) process, allows for correction of these non-uniform illumination patterns by means of a so-called point-spread function (PSF).

We apply MDD to surface-wave data recorded by the Malargüe seismic array in western Argentina (Fig. a & b). TN stations (Fig. c) act as virtual sources whose responses are retrieved at the TE stations. Time windows dominated by surface-wave noise traveling in a favorable (i.e. eastward) direction are selected through a frequency-dependent slowness analysis along the two receiver lines. From the selected time windows, virtual-source responses are retrieved by computation of ensemble-averaged crosscorrelations. Similarly, ensemble-averaged crosscorrelations between TN stations are computed: the point-spread function. We use the PSF to deconvolve the effect of illumination irregularities and the source function from the virtual-source responses. The combined effect of time-window selection and MDD results in more accurate surface-wave responses.

