

Urban solar potential analysis through semantic 3D city models

Xu, Longxiang; León-Sánchez, Camilo

Publication date 2024 Document Version Final published version

Published in Digitalisation of the Built Environment: 3rd 4TU-14UAS Research Day

Citation (APA)

Xu, L., & León-Sánchez, C. (2024). Urban solar potential analysis through semantic 3D city models. In G. Agugiaro, P. Savanović, & R. Sebastian (Eds.), *Digitalisation of the Built Environment: 3rd 4TU-14UAS Research Day* (pp. 55-58). TU Delft OPEN Publishing.

Important note

To cite this publication, please use the final published version (if applicable). Please check the document version above.

Copyright

Other than for strictly personal use, it is not permitted to download, forward or distribute the text or part of it, without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license such as Creative Commons.

Takedown policy

Please contact us and provide details if you believe this document breaches copyrights. We will remove access to the work immediately and investigate your claim.





Digitalisation of the Built Environment

3rd 4TU-14UAS Research Day

Extended abstracts

25 April 2024 Delft

Edited by Giorgio Agugiaro, Perica Savanović and Rizal Sebastian





Colophon

Digitalisation of the Built Environment 3rd 4TU-14UAS Research Day

Editors:

Giorgio Agugiaro¹, Perica Savanović², Rizal Sebastian³ ¹3D Geoinformation group, Department of Urbanism, Faculty of Architecture and Built Environment, Delft University of Technology – <u>g.agugiaro@tudelft.nl https://orcid.org/0000-0002-2611-4650</u> ² Research and Innovation Centre Engineering, Design and Computing, Inholland University of Applied Sciences – <u>perica.savanovic@inholland.nl https://orcid.org/0000-0003-3232-1362</u> ³ Future Urban Systems Research Group, The Hague University of Applied Sciences – <u>r.sebastian@hhs.nl https://orcid.org/0000-0003-1714-8418</u>

Keywords:

Built Environment, Artificial Intelligence, Robotics, Augmented/Virtual/Mixed Reality, Digital Twins

Published by:

TU Delft OPEN Publishing | Delft University of Technology, The Netherlands

DOI: https://doi.org/10.59490/mg.112

ISBN: 978-94-6366-912-2

Copyright statement:



This work is licensed under a Creative Commons Attribution 4.0
International (<u>CC BY 4.0</u>) licence.
© 2024 published by TU Delft OPEN Publishing on behalf of the authors
Copyright clearance made by the TU Delft Library copyright team.

Use of AI:

During the preparation of this work, the author(s) used Paperpal in order to language editing. After using this tool/service, the author(s) reviewed, edited and made the content their own as needed and take(s) full responsibility for the content of the publication.

Disclaimer:

Every attempt has been made to ensure the correct source of images and other potentially copyrighted material was ascertained, and that all materials included in this book have been attributed and used according to their license. Unless differently stated in the caption, all figures are attributed to the respective authors. If you believe that a portion of the material infringes someone else's copyright, please contact g.agugiaro@tudelft.nl

To cite this publication:

Agugiaro, G., Savanović, P., Sebastian, R. (2024) *Digitalisation of the Built Environment: 3rd 4TU/14UAS Research Day*. TU Delft OPEN Publishing, Delft University of Technology, The Netherlands.

Urban solar potential analysis through semantic 3D city models

Longxiang Xu¹, Camilo León-Sánchez²

¹ MSc in Geomatics, Delft University of Technology, Delft, The Netherlands – l.xu-18@student.tudelft.nl
² Delft University of Technology, Faculty of Architecture and Built Environment, Department of Urbanism, 3D Geoinformation Group, Delft, The Netherlands – c.a.leonsanchez@tudelft.nl

Keywords: Semantic 3D city models, Solar potential, UBEM, NTA8800

Extended Abstract

Currently, approximately 60% of the global population lives in urban areas (UN. Population Division, 2018). Incorrect quantification of the current and expected energy demands of buildings can lead to erroneous decisions and misguided planning for energy supply. Additionally, society is transitioning to adopting more sustainable energy sources to reduce environmental impacts. Solar gains play a major role in energy demand simulations. Therefore, it is important to perform precise calculations of the solar radiation for a given area of interest. However, this energy source faces challenges, such as shadowing, which rapidly decreases the performance of any solar panel, and it is constantly changing owing to the movement of the sun across the sky. Figure 1 shows a sketch of the considerations for computing shadowing calculations and the components of the solar irradiance.



Figure 1. Shadowing computation sketch (a) and solar irradiance components (b).

Shadowing analysis is crucial in urban planning (Palme *et al.*, 2020), especially for assessing the solar potential (Figure 1(a)). It helps identify suitable locations in urban areas by considering existing structures and future developments. This analysis is relevant for policymakers, as they encourage the population to adopt solar energy while ensuring efficient utilisation of available resources for a given location.

To perform solar potential analysis, it is essential to consider the geographical location and its surroundings. These include factors such as topography, construction, and vegetation (De Sá *et al.*, 2022). These city objects can be represented using semantic 3D city models [3DCM] (Agugiaro *et al.*, 2020), which provide datasets that allow for a coherent geometrical and semantic representation of urban features in a well-defined data structure. The solar irradiance received on a tilted surface can be categorised as direct beam irradiance, sky diffuse irradiance,

and (ground)reflected irradiance. Figure 1(b) illustrates these, with the diffuse components further divided into diffuse sky and diffuse horizon components.

We present the development of a solar potential analysis tool based on 3DCM. Our work uses the 3DBAG (Peters *et al.*, 2022), an open dataset containing 3D models of all buildings in the Netherlands. This dataset is available for downloading in several formats and multiple levels of detail (LoD) (0, 1.2, 1.3, 2.2) (Biljecki *et al.*, 2016). We used the pvGIS database (EU Science Hub, 2022) as the input weather data for our computations.

The hourly solar irradiance values were calculated using the Python package pylib (Holmgren *et al.*, 2018). These values are aggregated for each surface. Additionally, we aggregated the solar irradiance values for each month, as shown in Figure 2. The final values were compared according to the statistical parameters defined by Dutch standard NTA8800:2024 (NEN, 2024), which specifies a method for assessing the energy performance of buildings in the Netherlands. The statistical values provided by the standard were categorised based on the orientation and inclination of the boundary surfaces enclosing a building. Our simulations were conducted in the municipality of Rijssen-Holten, located in the eastern part of the Netherlands. The sunicipality has approximately 38000 inhabitants, corresponding to approximately 23000 buildings.

Figure 2 shows a scatter plot comparison for each boundary surface of buildings in the study area, with the red line representing the computed correlation coefficient. Figure 3 shows aggregated values per month for better comparison with norm values. Additionally, we include some statistical metrics such as MAE, n-RMSE, R, RMSE.



Figure 2. Scatter plot of monthly solar irradiance values.



Figure 4 shows the solar irradiance per surface in May for Rijssen-Holten. Both images used the same colour palette, ranging from blue (lowest value) to orange (highest value).



Figure 4. Rijssen-Holten solar irradiance output visualisation in May for NTA880 (a) and our computation (b).

The comparison of irradiance values between the NTA8800 standard and our method highlights the significant differences between purely statistical approaches and analytical methods that account for urban morphology. The correlation coefficient for the study area was 0.72, indicating a moderately linear relationship between the two values. This suggests that there is still a fundamental alignment in the irradiance patterns captured by both the datasets.

Error metrics in the bar plot in Figure 3 indicate that discrepancies between the NTA8800 values and our computed values were higher during warmer months. This divergence may be attributed to clearer skies during warmer seasons as opposed to predominantly overcast skies during colder skies. During colder seasons, the shadowing effect is not the primary source of energy loss, as overcast skies largely block direct beam solar irradiance, thereby reducing its impact (Tuononen *et al.*, 2019). One limitation of our approach is the inadequate treatment of light-ray diffusion and reflection, as illustrated in Figure 1(b). Our analysis simplifies the complex interactions between diffusion and reflection, which may affect the precision of our findings.

References

- Agugiaro, G., González, F.G.G., Cavallo, R. (2020). The City of Tomorrow from... the Data of Today. *ISPRS* International Journal of Geo-Information, 9, 554. <u>https://doi.org/10.3390/ijgi9090554</u>
- Biljecki, F., Ledoux, H., Stoter, J. (2016). An improved LOD specification for 3D building models. *Computers, Environment and Urban Systems*, 59, 25–37. <u>https://doi.org/10.1016/j.compenvurbsys.2016.04.005</u>
- De Sá, B.A., Dezuo, T., Ohf, D. (2022). Shadow Modelling Algorithm for Photovoltaic Systems: Extended Analysis and Simulation. *Journal of Control, Automation and Electrical Systems, 33*, 1507–1518. https://doi.org/10.1007/s40313-022-00905-2
- EU Science Hub (2022) PVGIS Online Tool [WWW Document]. Photovolt. Geogr. Inf. Syst. URL <u>https://joint-research-centre.ec.europa.eu/pvgis-online-tool_en</u> (Last accessed 31 May 2024)
- Holmgren, W.F., Hansen, C.W., Mikofski, M.A. (2018). pvlib python: a python package for modeling solar energy systems. *Journal of Open Source Software*, 3(29), 884. <u>https://doi.org/10.21105/joss.00884</u>
- Nederlands Normalisatie Instituut (2024). Energy performance of buildings Determination method (NTA 8800:2024 nl). <u>https://www.nen.nl/en/nta-8800-2024-nl-320123</u>
- Palme, M., Privitera, R., Rosa, D.L. (2020). The shading effects of Green Infrastructure in private residential areas: Building Performance Simulation to support urban planning. *Energy Build*. 229, 110531. <u>https://doi.org/10.1016/j.enbuild.2020.110531</u>

- Peters, R., Dukai, B., Vitalis, S., van Liempt, J., Stoter, J. (2022). Automated 3D Reconstruction of LoD2 and LoD1 Models for All 10 Million Buildings of the Netherlands. *Photogrammetic Engineering & Remote Sensing*, 88(3), 165–170. <u>https://doi.org/10.14358/PERS.21-00032R2</u>
- Tuononen, M., O'Connor, E.J., Sinclair, V.A. (2019). Evaluating solar radiation forecast uncertainty. *Atmospheric Chemistry and Physics*, 19(3), 1985–2000. <u>https://doi.org/10.5194/acp-19-1985-2019</u>
- UN. Population Division (2018). The World's Cities in 2018. United Nations, New York, USA.