

Delft University of Technology

# High sensitive CVD graphene-based gas sensors operating under environmental conditions

Ricciardella, Filiberto; Vollebregt, Sten; Polichetti, T.; Alfano, B.; Massera, E.; Sarro, Lina

**Publication date** 2017

**Document Version** Accepted author manuscript

**Citation (APA)** Ricciardella, F., Vollebregt, S., Polichetti, T., Alfano, B., Massera, E., & Sarro, L. (2017). *High sensitive CVD* graphene-based gas sensors operating under environmental conditions. 1-1. Abstract from Graphene 2017, Barcelona, Spain.

### Important note

To cite this publication, please use the final published version (if applicable). Please check the document version above.

Copyright

Other than for strictly personal use, it is not permitted to download, forward or distribute the text or part of it, without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license such as Creative Commons.

Takedown policy

Please contact us and provide details if you believe this document breaches copyrights. We will remove access to the work immediately and investigate your claim.

This work is downloaded from Delft University of Technology. For technical reasons the number of authors shown on this cover page is limited to a maximum of 10.

# High sensitive CVD graphene-based gas sensors operating under environmental conditions

# Filiberto Ricciardella<sup>1</sup>

Sten Vollebregt<sup>1</sup>, Tiziana Polichetti<sup>2</sup>, Brigida Alfano<sup>2</sup>, Ettore Massera<sup>2</sup> and Pasqualina M. Sarro<sup>1</sup>.

<sup>1</sup>Delft University of Technology, Feldmannweg 17, 2628 CT, Delft, The Netherlands <sup>2</sup>ENEA, Piazzale Enrico Fermi 1, I – 80055 Portici (Napoli), Italy

## filiberto.ricciardella@gmail.com

Graphene has been widely demonstrated to be a perfect candidate for gas sensing applications thanks to the structural and electronic properties [1]. In this work, we present calibrated graphene-based sensors able to detect NO<sub>2</sub> in the concentration range 0.1 – 1.5 ppm (parts-per-million) and operating under environmental conditions, i.e. room temperature (RT) and 50% relative humidity (RH). With a limit of detection (LOD) down to 150 ppb (Fig. 1), the findings are comparable with the best performances reported in the literature [1]. The chemiresistive devices, realized by the innovative transfer-free process [2], were demonstrated to work in the aforementioned conditions, keeping RH at 50% [1]. Here, the behavior of sensors exposed to large RH variation were further analysed. Devices having same graphene-bar length (206 µm) and different width (2, 5, 10 µm) (inset of Fig. 1), were overall electrically characterized and tested and the obtained findings will be presented. The RH effects were proven to be negligible with respect to the sensors performance (Fig. 2). Therefore, for ranges of RH variations shorter than 30%, the current responses were demonstrated to be related only to the graphene-analyte interaction.

# References

 F. Ricciardella, S. Vollebregt, T. Polichetti, B. Alfano, E. Massera, P.M. Sarro, Proceedings of IEEE Sensors Conference 2016, ISBN: 978-1-4799-8287-5, 697-699 [2] S. Vollebregt, B. Alfano, F. Ricciardella, A. J. M. Giesbers, Y. Grachova, H. W. van Zeijl, T. Polichetti, P. M. Sarro, Journal, IEEE 29th International Conference on MEMS (2016) 17-20



Figure 1: calibration curve of graphene-based chemi-resistive sensor towards NO<sub>2</sub>. Right-down inset shows one device geometry (length=206  $\mu$ m, width=5  $\mu$ m). Current dynamic behavior of sensor upon exposure to 4 min-long gas pulses (left-up inset). The current is normalized to the value I<sub>0</sub> during the gas inlet of the first pulse exposure.



